



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

187 ULTRA-FAST TAB 22-18 TPBR

Ultra-Fast | 187

2-521102-2

TE Internal Number: 2-521102-2

Always EU RoHS/ELV Compliant

Terminal Style **Tab**

Mating Tab Width **4.75 mm [.187 in]**

Mating Tab Thickness **.51 mm [.02 in]**

Wire Insulation Diameter (Max) **3.43 mm [.135 in]**

Wire Size (AWG) **22 – 18**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[TAB ASSEMBLY,ULTRA-FAST, 4.75 \[.187\] SERIES,22-18 AWG](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

Product Specifications

Product Specification

[Ultra-Fast Fully Insulated FASTON Tab Terminals](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-521102-2_07172013319_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Disconnect Type	Quick Disconnect Pin
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable

Configuration Features	Paired	No
	Terminal Angle	Straight

Electrical Characteristics	Voltage (Max) (V)	600
----------------------------	-------------------	------------

Body Features	Plating Material	Tin
	Fully Insulated	Yes

Contact Features	Terminal Style	Tab
	Terminal Orientation	Straight
	Contact Plating Material	Tin

Termination Features	Crimp Type	F-Crimp
----------------------	------------	----------------

Dimensions	Mating Tab Width	4.75 mm [.187 in]
	Mating Tab Thickness	.51 mm [.02 in]
	Wire Insulation Diameter (Max)	3.43 mm [.135 in]
	Wire Size (AWG)	22 – 18
	Wire Size (mm ²)	.32 – .82
	Overall Length	20.14 mm [.793 in]

Usage Conditions	Operating Temperature Range (°C)	105
------------------	----------------------------------	------------

Industry Standards	UL Rating	Listed
	UL Flammability Rating	UL 94V-2

Packaging Features	Packaging Method	Reel
--------------------	------------------	-------------

Packaging Quantity

1500

Other

Barrel Color





Red

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>CRIMP QUICK DISCONNECTS</p>  <p>ULTRAFAST 250 ASSY TAB 22-18 AWG TPBR 2-521055-2</p> <p>Save to List Find Similar Products</p>	<p>CRIMP QUICK DISCONNECTS</p>  <p>250 SER FAST REC 24-20 016TPBR 61368-1</p> <p>Save to List Find Similar Products</p>	<p>CRIMP QUICK DISCONNECTS</p>  <p>ULTRAFAST 187 ASSY REC 22-18 TPBR LP 2-520182-2</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD CONNECTOR HOUSINGS</p>  <p>07P SL156 HSG W/LCK RMP & TABS 770849-7</p> <p>Save to List Find Similar Products</p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Products - 1 Results

[View All](#)

Compare 0/10

Relation Type

RELATIONSHIP

Toolings
Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

OC-AT-S-FA-176D-001-0056 - 2151034-2
TE INTERNAL NUMBER: 2151034-2

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **No**

Applicator Style **OCEAN - Atlantic**

Applicator Feed Style **Side Feed**

