



RJ45 CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

8/8 MOD JACK ASSY SE

SE

2-5338556-1

TE Internal Number: 2-5338556-1

Always EU RoHS/ELV Compliant

Port Configuration **Single**

Shielded **Yes**

Jack Configuration **1 x 1**

Connector Style **Jack**

Inverted Jack Face **No**

Product Drawings

[8 Pos. Modular Jack Side Entry Fully Shielded With Insulation Plate](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[82066 - Modular Jacks And MRJ21 Product Catalog - Single Port Modular Jacks Section](#)

PDF
English

[1-1773464-9_MODULAR_JACKS_SINGLE_PORT_PCB_MOUNT](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2-5338556-1_05042015454_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Shielded	Yes
	Connector Style	Jack
	Performance Category	Cat 3
	Profile	Low
	PCB Mounting Orientation	Side Entry (Right Angle)
	Connector Type	Connector Assembly
	Product Type	Connector
	Latch Style	Standard
	Jack Type	RJ45
	Grounding Options	Panel Ground and PCB Ground
	LED	Without
Panel Stops	Without	
Configuration Features	Port Configuration	Single
	Jack Configuration	1 x 1
	Number of Positions	8
	Number of PCB Ground Tabs	2
	Preloaded	Yes
	Keyed	No
	Panel Ground Location	Top and Side, Top
Body Features	Inverted Jack Face	No
	PCB Ground Tab Location	3.05 mm [.12 in]
	Shield Plating Finish	Bright
	Shield Material	Brass
	Color	Black
	Shield Plating Material	Tin
Contact Features	Number of Contacts Loaded	8
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
Termination Features	Termination Method to PC Board	Solder
Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	With
	Flanged	No





Housing Features	Housing Material	PBT Polyester
	Housing Color	Black
Dimensions	Height	12.1 mm [.476 in]
	PCB Thickness (Recommended)	1.6 mm [.062 in]
	PCB Tail Length	3.1 mm [.122 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	190
	Packaging Method	Tray, Tray/Box
Other	Comment	Staggered side panel grounds so 2 connectors can be placed side by side, With insulation plate.

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>PCB D-SUB CONNECTORS</p>  <p>9P.HDP20 REC.ASSY. 1-106505-2</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>SURFACE MOUNT RESISTORS</p>  <p>RP 2B 24R9 0.1% 15PPM CUT LENGTH RP73D2B24R9BTG</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p>  <p>0.8FH, R05H.5, 100, 08/Sn, TR, SC 5177985-4</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>SURFACE MOUNT RESISTORS</p>  <p>RN 0805 4K64 0.1% 10PPM 1KRL RN73C2A4K64BTDF</p> <p>Save to List</p> <p>Find Similar Products</p>
---	--	---	---