



# HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

## 05P MTA100 SHRDED HDR ASSY SN

MTA | MTA-100

2-644486-5

TE Internal Number: 2-644486-5

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

Number of Positions **5**

PCB Mounting Orientation **Vertical**

PCB Mounting Style **Through Hole**

Number of Rows **1**

Active

PRODUCT DRAWING  
English

3D PDF

### Product Drawings

MTA-100 SHROUDED HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT POST, TIN OR TIN LEAD PLATED

PDF  
English

### CAD Files

Customer View Model

3D\_STP.ZIP  
English

3D PDF

PDF  
3D

Customer View Model

2D\_DXF.ZIP  
English

Customer View Model

3D\_IGS.ZIP  
English

### Catalog Pages/Data Sheets

MTA, CST-100 II, SL-156 And AMP Economy Power (EP) Connectors

PDF  
English

### Product Specifications

Product Specification

Connector, MTA-100

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

PCB Mounting Orientation

Vertical

Product Type

Connector

	Connector Type	<b>Header</b>
	Connector System	<b>Wire-to-Board</b>
	Strain Relief	<b>Without</b>
	Sealed	<b>No</b>
	Connector Style	<b>Plug</b>
	Applies To	<b>Printed Circuit Board</b>
Configuration Features	Number of Positions	<b>5</b>
	Number of Rows	<b>1</b>
	Backwall/Post Interruptions	<b>Without</b>
Electrical Characteristics	Operating Voltage (VAC)	<b>250</b>
Body Features	Header Type	<b>Shrouded</b>
Contact Features	Contact Mating Area Plating Material	<b>Tin</b>
	Contact Mating Area Plating Thickness	<b>3.81 – 6.3 µm [ 150 – 250 µin ]</b>
	Underplate Material	<b>Nickel</b>
	Contact Termination Area Plating Thickness	<b>3.81 – 6.3 µm [ 150 – 250 µin ]</b>
	Underplate Material Thickness	<b>1.27 µm, 50 µin</b>
	Contact Style	<b>Straight</b>
	Contact Shape	<b>Square</b>
	Tail Plating Material	<b>Tin</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Tail Plating Thickness	<b>3.81 – 6.3 µm [ 150 – 250 µin ]</b>
	Contact Type	<b>Pin</b>
	Contact Current Rating (A)	<b>5</b>
	Contact Layout	<b>Inline</b>
	Contact Termination Area Plating Material Finish	<b>Matte</b>
Contact Base Material	<b>Copper Alloy</b>	
Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
	Termination Method to Wire/Cable	<b>Solder</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Alignment	<b>With</b>

PCB Mount Alignment Type	<b>Pegs</b>
Mating Retention	<b>With</b>
PCB Mount Retention	<b>With</b>
PCB Mount Retention Type	<b>Tabs</b>
Contact Retention	<b>Without</b>
Mating Alignment Type	<b>Polarizing Tab</b>
Mating Retention Type	<b>Friction Lock</b>
Panel Mount Retention	<b>Without</b>
Mating Alignment	<b>With</b>

---

Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Style	<b>Friction Lock</b>
	Housing Material	<b>Polyester - GF</b>

---

Dimensions	Tail Length	<b>3.56 mm [ .14 in ]</b>
	Mating Post Length	<b>5.1 mm [ .2 in ]</b>
	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Height	<b>10.41 mm [ .41 in ]</b>
	Length	<b>14.83 mm [ .584 in ]</b>

---

Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
------------------	-----------------------------	--------------------------------------

---

Operation/Application	For Use With	<b>MTA .100 Connector Assembly</b>
-----------------------	--------------	------------------------------------

---

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	UL File Number	<b>E28476</b>
	CSA Rating	<b>Certified</b>
	Agency/Standard	<b>CSA, UL</b>
	CSA File Number	<b>LR7189</b>
	UL Rating	<b>Recognized</b>

---

Packaging Features	Packaging Method	<b>Bag/Box</b>
	Packaging Quantity	<b>500</b>

---

Product Compliance [Statement of Compliance](#)  
PDF

