

## **HEADERS & RECEPTACLES**





















**PRODUCT DRAWING** 



3D PDF

TE CONNECTIVITY (TE)

06P MTA100 SHRDED HDR ASSY SN

MTA | MTA-100

2-644486-6

TE Internal Number: 2-644486-6

Always EU RoHS/ELV Compliant

Centerline 2.54 mm [.1 in]

Number of Positions 6

PCB Mounting Orientation Vertical

PCB Mounting Style Through Hole

Number of Rows 1

**Product Drawings** 

MTA-100 SHROUDED HEADER ASSEMBLY, FRICTION LOCK, STRAIGHT POST,

TIN OR TIN LEAD PLATED

PDF English

**CAD Files** 

Customer View Model

3D\_STP.ZIP English

3D PDF

**Customer View Model** 

2D\_DXF.ZIP English

**Customer View Model** 

3D\_IGS.ZIP English

Catalog Pages/Data Sheets

MTA, CST-100 II, SL-156 And AMP Economy Power (EP) Connectors

PDF **English** 

**Product Specifications** 

**Product Specification** Connector, MTA-100

PDF **English** 

Product Environmental Compliance

TE Material Declaration MD\_2-644486-6\_05172013104\_dmtec

PDF English

Product Type Features	PCB Mounting Orientation	Vertical
	Product Type	Connector
	Connector Type	Header
	Connector System	Wire-to-Board
	Strain Relief	Without
	Sealed	No
	Connector Style	Plug
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	6
	Number of Rows	1
	Backwall/Post Interruptions	Without
Electrical Characteristics	Operating Voltage (VAC)	250
Body Features	Header Type	Shrouded
Contact Features	Contact Mating Area Plating Material	Tin
	Contact Mating Area Plating Thickness	3.81 – 6.3 μm [ 150 – 250 μin ]
	Underplate Material	Nickel
	Contact Termination Area Plating Thickness	3.81 – 6.3 μm [ 150 – 250 μin ]
	Underplate Material Thickness	1.27 μm, 50 μin
	Contact Style	Straight
	Contact Shape	Square
	Tail Plating Material	Tin
	Contact Termination Area Plating Material	Tin
	Tail Plating Thickness	3.81 – 6.3 µm [ 150 – 250 µin ]
	Contact Type	Pin
	Contact Current Rating (A)	5
	Contact Layout	Inline
	Contact Termination Area Plating Material Finish	Matte
	Contact Base Material	Copper Alloy
Termination Features	Termination Method to PC Board	Through Hole - Solder

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Alignment	With
	PCB Mount Alignment Type	Pegs
	Mating Retention	With
	PCB Mount Retention	With
	PCB Mount Retention Type	Tabs
	Contact Retention	Without
	Mating Alignment Type	Polarizing Tab
	Mating Retention Type	Friction Lock
	Panel Mount Retention	Without
	Mating Alignment	With
Housing Features	Centerline	2.54 mm [ .1 in ]
	Housing Color	Black
	Housing Style	Friction Lock
	Housing Material	Polyester - GF
	-	•
Dimensions	Tail Length	3.56 mm [ .14 in ]
	Mating Post Length	5.1 mm [ .2 in ]
	PCB Thickness (Recommended)	1.6 mm [ .063 in ]
	Height	10.41 mm [ .41 in ]
	Length	17.37 mm [ .684 in ]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	MTA .100 Connector Assembly
Industry Standards	UL Flammability Rating	UL 94V-0
	UL File Number	E28476
	CSA Rating	Certified
	Agency/Standard	CSA, UL
	CSA File Number	LR7189
	UL Rating	Recognized
Packaging Features	Packaging Method	Package
	Packaging Quantity	1000

# Statement of Compliance

#### VIEW ALL PRODUCT COMPLIANCE

**Products** - 56 Results

View All

See All Mating Products

See All Mating Products



Relation Type

#### RELATIONSHIP

## **Mating Products** Used to identify Mating Parts





PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles MTA | MTA-100

06P MTA100 CONN ASSY BLK LF - 3-644312-6

✓ Active

#### Always EU RoHS/ELV Compliant

Centerline 2.54 mm

Number of Positions 6

Number of Rows 1

Contact Mating Area Plating

Material **Tin** 

Contact Mating Area Plating

Material Finish Matte

RELATIONSHIP

## **Mating Products** Used to identify Mating Parts

PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles MTA | MTA-100

06 CIR MTA-100 ASSY ON TAPE - 641311-6

✓ Active

Not EU RoHS or ELV Compliant

Centerline 2.54 mm

Number of Positions 6

Number of Rows 1

Contact Mating Area Plating

Material Tin-Lead

Contact Mating Area Plating Material Finish Bright

RELATIONSHIP

### **Mating Products**

Used to identify Mating Parts

See All Mating Products

PRODUCT - MATING PRODUCTS

Connectors M/T P Hondors & Possentacion

Always Ell Dalle/Ell/ Compliant



Connectors - w-1-b meaders & Receptacies MTA | MTA-100

06P MTA100 CONN ASSY BLK LF - 3-644578-6
TE INTERNAL NUMBER: 3-644578-6

Always EU NOD3/ELV COMPILANT

Centerline 2.54 mm

Number of Positions 6

Number of Rows 1

Contact Mating Area Plating

Material **Tin** 

Contact Mating Area Plating

Material Finish Matte