



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

22POS, MICRO MNL, RCPT HSG

MATE-N-LOK | Micro MATE-N-LOK

2-794617-2

TE Internal Number: 2-794617-2

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Board, Wire-to-Wire**

Applies To **Printed Circuit Board, Wire/Cable**

Number of Positions **22**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

RECEPTACLE HOUSING, 2 TO 24 POSITION, DUAL ROW, MICRO MATE-N-LOK

PDF
English

CAD Files

3D PDF

PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

PDF
English

1773458-4_MICRO_MATE_N_LOK_CONNECTOR_SYSTEM_ORG

PDF
English

Product Specifications

Product Specification

3 Mm Micro MATE-N-LOK Connector

PDF
English

Application Specification

Micro MATE-N-LOK Connectors





PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Receptacle
	Contact Type	Socket
<hr/>		
Configuration Features	Number of Positions	22
	Centerline	3 mm [.118 in]
	Number of Rows	2
	Row-to-Row Spacing	3 mm [.118 in]
<hr/>		
Electrical Characteristics	Operating Voltage (VAC)	250
<hr/>		
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Black
	Housing Material	Nylon 66/6
<hr/>		
Operation/Application	Connector System	Wire-to-Board, Wire-to-Wire
	Applies To	Printed Circuit Board, Wire/Cable
	Operating Temperature	-40 – 105 °C [-40 – 221 °F]
<hr/>		
Industry Standards	UL Rating	Recognized
	VDE Tested	Yes
	CSA Rating	Certified
	CSA File Number	LR7189
	Agency/Standard Number	E28476
	Agency/Standard	CSA, UL
<hr/>		
Packaging Features	Packaging Method	Package
	Packaging Quantity	1
<hr/>		
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

POWER CONTACTS	RECTANGULAR POWER CONNECTORS	POWER CONTACTS	WIRE-TO-BOARD CONNECTOR HOUSINGS
----------------	------------------------------	----------------	----------------------------------

 <p>PIN CONT 20-24 30 GOLD L/P 794612-3</p> <p>Save to List Find Similar Products</p>	 <p>22P MICRO MNL ASSY, VRT, HDR, LF 5-794630-2</p> <p>Save to List Find Similar Products</p>	 <p>MICRO MNL RPT CNT, LS PC, TIN 794610-1</p> <p>Save to List Find Similar Products</p>	 <p>CT MT REC ASSY 4P GRAY 2-179694-4</p> <p>Save to List Find Similar Products</p>
---	---	--	--

Products - 56 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Standard Rectangular Connectors MATE-N-LOK Micro MATE-N-LOK 22POS MICRO MNL ASSY, R/A, HDR - 2-794619-2 TE INTERNAL NUMBER: 2-794619-2</p> <p>✓ Active</p> <p>Not EU RoHS or ELV Compliant</p> <p>Product Type Connector</p> <p>Mating Alignment With</p> <p>Mating Alignment Type Polarization</p> <p>Mating Retention With</p> <p>Mating Retention Type Locking Tab</p>
--	--

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Standard Rectangular Connectors MATE-N-LOK Micro MATE-N-LOK 22POS MICRO MNL ASSY, VRT, SMT - 2-794636-2 TE INTERNAL NUMBER: 2-794636-2</p> <p>✓ Active</p> <p>Not EU RoHS or ELV Compliant</p> <p>Product Type Connector</p> <p>Mating Alignment With</p> <p>Mating Alignment Type Polarization</p> <p>Mating Retention With</p> <p>Mating Retention Type Locking Tab</p>
---	--

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors
MATE-N-LOK | Micro MATE-N-LOK

PANEL MT DBL ROW HSG 22 POS - 2-794615-2

TE INTERNAL NUMBER: 2-794615-2

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Panel,
Wire-to-Wire**

Applies To **Panel, Wire/Cable**

Number of Positions **22**