



TE CONNECTIVITY (TE)
MQS STIFTE MAGAZ
MQS

2-963964-4
TE Internal Number: 2-963964-4

Always EU RoHS/ELV Compliant

Terminal Style **Pin/Tab**

Mating Tab Width **.63 mm [.025 in]**

Mating Tab Thickness **.64 mm [.024 in]**

Primary Locking Feature **None**

Interface Plating **Tin (Sn)**

Active

[Product Drawing](#)
English

[3D PDF](#)

Product Drawings

[MQS ACTION PIN FOR 1mm HOLE ACTION PIN Fuer 1mm Loch, Freistehend](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Primary Locking Feature

None

Contact Features

Terminal Style

Pin/Tab

Mating Tab Width

.63 mm [.025 in]

Mating Tab Thickness

.64 mm [.024 in]

Interface Plating

Tin (Sn)

Typical Current Rating (A)

7.5

Termination Features	Termination Method	Press-Fit
Usage Conditions	Operating Temperature (Max) (°C)	80, 85, 90, 100, 105, 110, 120, 125
	Operating Temperature (Max) (°F)	176, 185, 194, 212, 221, 230, 248, 257
	Operating Temperature Range	-40 – 125 °C [-40 – 257 °F]
Packaging Features	Packaging Method	Reel
	Packaging Quantity	50000
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	