



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

SEMI-HARD TRAY DDR3 204P 5.2H STD

DDR3 SODIMM | STA , STA.20

2013289-1

TE Internal Number: 2013289-1

Always EU RoHS/ELV Compliant

DRAM Type **Double Data Rate (DDR) 3**

Stack Height **5.2 mm [.205 in]**

Module Orientation **Right Angle**

PCB Mounting Style **Surface Mount**

Centerline **.6 mm [.024 in]**

Product Drawings

[DDR3 SODIMM SOCKET 0.6mm PITCH 204POS 5.2mm HEIGHT STANDARD TYPE](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[6-1773457-3_DDR3_DIMM_SOCKETS](#)

PDF

[DDR3 DIMM Sockets Flyer 6-1773454-7 05/09](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2013289-1_1109201525_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Row-to-Row Spacing	8.2 mm [.322 in]
	Product Type	Socket
	Applies To	Printed Circuit Board
Configuration Features	Module Orientation	Right Angle
	Number of Positions	204
	Number of Rows	2
	Number of Bays	2
	Center Key	Offset Left
	Keying	Standard
	Number of Keys	1
Electrical Characteristics	DRAM Voltage (V)	1.5
Signal Characteristics	SGRAM Voltage (V)	1.5
Body Features	Ejector Location	Both Ends
	Module Key Type	SGRAM
	Latch Material	Stainless Steel
	Ejector Type	Locking
	Latch Plating Material	Tin
Contact Features	Contact Mating Area Plating Material	Gold Flash
	Solder Tail Contact Plating Material	Gold
	Contact Base Material	Copper Alloy
	Socket Style	SO DIMM
	Socket Type	Memory Card
Termination Features	Insertion Style	Cam-In
Mechanical Attachment	PCB Mounting Style	Surface Mount
	PCB Mount Retention	With
	PCB Mount Retention Type	Solder Peg
Housing Features	Centerline	.6 mm [.024 in]
	Housing Color	Black
	Housing Material	High Temperature Thermoplastic

Dimensions	Stack Height	5.2 mm [.205 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Semi-Hard Tray Assembly
	Packaging Quantity	20
Other	Comment	With floating page.

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)