

HARD METRIC BACKPLANE CONNECTORS



✓ Active

PRODUCT DRAWING
English
3D PDF

te connectivity (te) zd Plus, 4 pair, receptacle assy z-PACK | HM-Zd+

2065657-1 TE Internal Number: 2065657-1

Always EU RoHS/ELV Compliant

Data Rate (Gb/s) **≤12**

Number of Columns **10** Number of Pairs **40**

Centerline (mm) **2.5**

Number of Positions 80

Product Drawings	ASSEMBLY, Z-Pack Hm-Zd Plus, RECEPTACLE, 4 PAIR PDF English		
CAD Files	3D PDF PDF 3D		
	Customer View Model 2D_DXF.ZIP English		
	Customer View Model 3D_IGS.ZIP English		
	Customer View Model 3D_STP.ZIP English		
Catalog Pages/Data Sheets	5-1773463-9_Z-PACK_HM-ZD_PLUS_CONNECTOR ^{PDF} English		
Product Specifications			
Product Specification	Two, Three And Four Pair HM-Zd Connectors		
Application Specification	English Z-PACK Hard Metric (HM)-Zd And HM-Zd Plus 2-, 3-, And 4-Pair Connector Systems PDF		
Qualification Test Report	English Two, Three And Four Pair HM-Zd Connectors PDF English		

Product Environmental Compliance

TE Material Declaration

MD_2065657-1_01012014831_dmtec PDF English

y b f v

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Right Angle
	Shielded	No
	Connector Style	Plug
	Make First / Break Last	No
	Connector Type	Connector Assembly
	Applies To	Printed Circuit Board
Configuration Features	Number of Columns	10
	Number of Pairs	40
	Number of Positions	80
	Pairs per Column	4
	Selectively Loaded	Νο
Signal Characteristics	Data Rate (Gb/s)	≤12
Body Features	Shield Material	Phosphor Bronze
Contact Features	Contact Base Material	Copper-Nickel-Silicon
	Contact Configuration	Compliant Pin
	Contact Type	Socket
Termination Features	Termination End Plating Material Finish	Matte
	Termination Method	Press-Fit
	Termination End Plating Material	Tin over Nickel
	Contact Termination Type	Through Hole
	Interface Type	HM-Zd Plus
Housing Features	Centerline (mm)	2.5
	Housing Material	Polyester - GF
Dimensions	Module Length (mm)	24.9
ndustry Standards	UI Elammability Rating	UL 94V-0

UL Flammability Rating

Packaging Features	Packaging Method Packaging Quantity	Tube 20
Product Compliance	Statement of Compliance PDF	

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

HARD METRIC BACKPLANE CONNECTORS	SFP/SFP+/ZSFP+	HARD METRIC BACKPLANE CONNECTORS	RECTANGULAR POWER CONNECTORS
			Contraction of the second s
HMZD 4PR RA HDR 80P ASSY LF 6469048-1	SFP+assy 2x6 Spring Fingers 4 LP Sn 2007562-5	HM-ZD 4PR HDR 80P 5.2MM 6469002-1	07P MTA156 CONN ASSY 22AWG RED 3-643819-7
Save to ListFind Similar Products	Save to List	Save to ListFind Similar Products	Save to List
<			