



## CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### METRIMATE SOCKET 19 POSN

AMP | Metrimate

208210-2

TE Internal Number: 208210-2  
Alias ID: 049004-000, AMPS-0-0208210-2

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Board, Wire-to-Panel, Wire-to-Wire**

Centerline **5.08 mm [ .2 in ]**

Row-to-Row Spacing **4.39 mm [ .173 in ]**

Number of Positions **19**

Number of Rows **5**

#### Product Drawings

##### SOCKET HOUSING, 19 POSN, METRIMATE

PDF  
English

#### CAD Files

##### Customer View Model

2D\_DXF.ZIP  
English

##### 3D PDF

PDF  
3D

##### Customer View Model

3D\_IGS.ZIP  
English

##### Customer View Model

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

##### METRIMATE\_PIN\_SOCKET\_CATALOG

PDF  
English

#### Product Specifications

Application Specification

##### APPLICATION SPECIFICATION, METRIMATE DRAWER CONNECTORS

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

##### MD\_208210-2\_0707201428\_dmtec

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	<b>Wire-to-Board, Wire-to-Panel, Wire-to-Wire</b>
	Row-to-Row Spacing	<b>4.39 mm [ .173 in ]</b>
	Connector Style	<b>Plug</b>
	Applies To	<b>Panel, Printed Circuit Board, Wire/Cable</b>
	Wire/Cable Type	<b>Discrete Wire</b>
	Wire Type	<b>Stranded</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Housing</b>
Configuration Features	Number of Positions	<b>19</b>
	Number of Rows	<b>5</b>
	Connector Configuration	<b>Drawer</b>
Electrical Characteristics	Operating Voltage	<b>600 VAC [ 600 VDC ]</b>
Contact Features	Contact Type	<b>Socket</b>
Mechanical Attachment	Panel Mount Retention Type	<b>Screw Mount</b>
	Panel Mount Retention	<b>With</b>
Housing Features	Centerline	<b>5.08 mm [ .2 in ]</b>
	Housing Material	<b>Polyester</b>
	Housing Color	<b>Black</b>
Dimensions	Length (mm)	<b>61.04</b>
	Width (mm)	<b>36.88</b>
	Panel Thickness	<b>.031 – .091 in, .8 – 2.3 mm</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 130 °C [ -67 – 266 °F ]</b>
Operation/Application	For Use With	<b>Hardware 208211-1 or -4, Receptacle Housing</b>
Industry Standards	UL Rating	<b>Certified, Recognized</b>
	VDE Tested	<b>Yes</b>
	Agency/Standard	<b>CSA, UL</b>
	UL File Number	<b>E28476</b>

UL Flammability Rating

**UL 94V-0**

Packaging Features

Packaging Quantity

**1**

Packaging Method

**Package**

Other

Comment



**Hardware not supplied.**

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

POWER CONTACTS	RECTANGULAR CONNECTOR HOUSINGS	RECTANGULAR POWER CONNECTORS	RECTANGULAR POWER CONNECTORS
			
III+ SKT, 18-14, TIN , STRIP 1-66358-8	METRIMATE PIN HSG 19 POSN 208209-2	10P MINI UMNL HDR ASSY D/R VRT 1-770743-0	12P MINI UMNL HDR W/DH SN LF 1-794066-0
<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>