



CONNECTOR HOUSINGS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

METRIMATE SKT HSG 25P

AMP | Metrimate

211150-1

TE Internal Number: 211150-1

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Board, Wire-to-Panel, Wire-to-Wire**

Centerline **5.08 mm [.2 in]**

Row-to-Row Spacing **5.08 mm [.173 in]**

Number of Positions **25**

Number of Rows **5**

Product Drawings

SOCKET HOUSING, 25 POSN METRIMATE

PDF (TIFF AVAILABLE)
English

SOCKET HOUSING, 25 POSN METRIMATE

PDF (TIFF AVAILABLE)
English

CAD Files

3D PDF

PDF
English

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

METRIMATE_PIN_SOCKET_CATALOG

PDF
English

Product Specifications

Product Specification

ACTION PIN Metrimate Drawer Connector

PDF
English

Application Specification

APPLICATION SPECIFICATION, METRIMATE DRAWER CONNECTORS

PDF
English

Qualification Test Report

Connector, Action Pin, Metrimate, Drawer

PDF
English

Connector, Action Pin, Metrimate, Drawer

PDF
Japanese

Connector, Action Pin, Metrimate, Drawer

Product Environmental Compliance

TE Material Declaration

[MD_211150-1_12302013223_dmtec](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	Wire-to-Board, Wire-to-Panel, Wire-to-Wire
	Row-to-Row Spacing	5.08 mm [.173 in]
	Connector Style	Plug
	Applies To	Panel, Printed Circuit Board, Wire/Cable
	Wire/Cable Type	Discrete Wire
	Wire Type	Stranded
	Product Type	Connector
	Connector Type	Housing

Configuration Features	Number of Positions	25
	Number of Rows	5
	Connector Configuration	Drawer

Electrical Characteristics	Operating Voltage (VAC)	600
----------------------------	-------------------------	------------

Body Features	Material	Polyester
	Color	Black

Contact Features	Contact Type	Socket
------------------	--------------	---------------

Mechanical Attachment	Panel Mount Retention Type	Screw Mount
	Panel Mount Retention	With

Housing Features	Centerline	5.08 mm [.2 in]
	Housing Material	Polyester
	Housing Color	Black

Dimensions	Length (mm)	30.78
	Height (mm)	62.53

Height (mm)	30.78
Width (mm)	30.78
Panel Thickness	.031 – .091 in, .8 – 2.3 mm

Usage Conditions	Operating Temperature Range	-55 – 130 °C [-67 – 266 °F]
------------------	-----------------------------	-----------------------------

Operation/Application	For Use With	Hardware 208211-1 or -4, Receptacle Housing
-----------------------	--------------	---

Industry Standards	UL Rating	Certified, Recognized
	VDE Tested	Yes
	UL File Number	E28476
	Agency/Standard	CSA, UL
	UL Flammability Rating	UL 94V-0





Packaging Features	Packaging Quantity	1
	Packaging Method	Package

Other	Comment	Hardware not supplied.
-------	---------	------------------------

Product Compliance [Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>RECTANGULAR CONNECTOR HOUSINGS</p>  <p>PIN HSG, 25 POSN, METRIMATE 211149-1</p> <p>Save to List Find Similar Products</p>	<p>NEMA TERMINAL BLOCKS</p>  <p>M.D. END SECTION, FLAT BASE 1546163-1</p> <p>Save to List Find Similar Products</p>	<p>PRO-CRIMPER & DIES</p>  <p>PROCRMP TL W/DIE COMM .093 P/S 90871-1</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR CONNECTOR HOUSINGS</p>  <p>PLUG HSG, 4 POSN, METRIMATE 212608-1</p> <p>Save to List Find Similar Products</p>
---	--	---	---