



## CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### PLUG HSG,12 POSN,METRIMATE

METRIMATE | [Metrimate](#)

211758-1

TE Internal Number: 211758-1

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Board, Wire-to-Panel, Wire-to-Wire**

Centerline **5.08 mm [ .2 in ]**

Row-to-Row Spacing **5.08 mm [ .173 in ]**

Number of Positions **12**

Number of Rows **4**

#### Product Drawings

[Socket Hsg 12 Pos Metrimate](#)

PDF (**TIFF AVAILABLE**)  
English

[Socket Hsg 12 Pos Metrimate](#)

PDF (**TIFF AVAILABLE**)  
English

#### CAD Files

[3D PDF](#)

PDF  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[METRIMATE\\_PIN\\_SOCKET\\_CATALOG](#)

PDF  
English

#### Product Specifications

Application Specification

[APPLICATION SPECIFICATION, METRIMATE DRAWER CONNECTORS](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Row-to-Row Spacing	<b>5.08 mm [ .173 in ]</b>
	Connector Style	<b>Plug</b>
	Applies To	<b>Panel, Printed Circuit Board, Wire/Cable</b>
	Wire/Cable Type	<b>Discrete Wire</b>
	Wire Type	<b>Stranded</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Housing</b>
Configuration Features	Number of Positions	<b>12</b>
	Number of Rows	<b>4</b>
	Connector Configuration	<b>Drawer</b>
Electrical Characteristics	Operating Voltage (VAC)	<b>600</b>
Body Features	Material	<b>Polyester GF</b>
	Color	<b>Black</b>
Contact Features	Contact Type	<b>Socket</b>
Mechanical Attachment	Panel Mount Retention Type	<b>Screw Mount</b>
	Panel Mount Retention	<b>With</b>
Housing Features	Centerline	<b>5.08 mm [ .2 in ]</b>
	Housing Material	<b>Polyester GF</b>
	Housing Color	<b>Black</b>
Dimensions	Length (mm)	<b>49.33</b>
	Width (mm)	<b>30.23</b>
	Panel Thickness	<b>.031 – .091 in, .8 – 2.3 mm</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 130 °C [ -67 – 266 °F ]</b>
Operation/Application	For Use With	<b>Hardware 208211-1 or -4, Receptacle Housing</b>
Industry Standards	UL Rating	<b>Certified, Recognized</b>
	VDE Tested	<b>Yes</b>

Agency/Standard	<b>CSA, UL</b>
UL File Number	<b>E28476</b>
UL Flammability Rating	<b>UL 94V-0</b>

Packaging Features	Packaging Quantity	<b>1</b>
	Packaging Method	<b>Package</b>

Other	Comment	<b>Hardware not supplied.</b>
-------	---------	-------------------------------

Product Compliance [Statement of Compliance PDF](#)  
[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

RECTANGULAR CONNECTOR HOUSINGS	SOLDERSLEEVE SHIELD TERMINATORS	HEAT SHRINK TUBING	POWER CONTACTS
<p>RECEPT HSG, 12 POSN, METRIMATE 211759-1</p> <p> Save to List   Find Similar Products</p>	<p>B-155-3803 B-155-3803</p> <p> Save to List   Find Similar Products</p>	<p>QSZH-125-NR1-30MM QSZH-125-NR1-30MM</p> <p> Save to List   Find Similar Products</p>	<p>III+ PIN, 18-14, 30AU/FL, STRIP 1-66359-6</p> <p> Save to List   Find Similar Products</p>