



# CONNECTOR HOUSINGS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## PLG HSG, 3 POWR, 12 SGNL, METRI

AMP | Metrimate

213426-1

TE Internal Number: 213426-1

Always EU RoHS/ELV Compliant

Connector System **Wire-to-Board, Wire-to-Panel, Wire-to-Wire**

Centerline **5.08 mm [ .2 in ]**

Row-to-Row Spacing **4.39 mm [ .173 in ]**

Number of Positions **15**

Number of Rows **5**

### Product Drawings

[HOUSING, PLUG, DRAWER CONNECTOR, 15 POSITION METRIMATE](#)

PDF (TIFF AVAILABLE)  
English

[HOUSING, PLUG, DRAWER CONNECTOR, 15 POSITION METRIMATE](#)

PDF (TIFF AVAILABLE)  
English

### CAD Files

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

### Catalog Pages/Data Sheets

[Power Contacts](#)

PDF  
English

[METRIMATE\\_PIN\\_SOCKET\\_CATALOG](#)

PDF  
English

### Product Specifications

Product Specification

[CONNECTOR, POWER DRAWER](#)

PDF  
Japanese

Application Specification

[APPLICATION SPECIFICATION, METRIMATE DRAWER CONNECTORS](#)

PDF  
English

Qualification Test Report

[QUALIFICATION TEST REPORT](#)

PDF  
English

[QUALIFICATION TEST REPORT](#)

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector System	<b>Wire-to-Board, Wire-to-Panel, Wire-to-Wire</b>
	Row-to-Row Spacing	<b>4.39 mm [ .173 in ]</b>
	Connector Style	<b>Plug</b>
	Applies To	<b>Panel, Printed Circuit Board, Wire/Cable</b>
	Wire/Cable Type	<b>Discrete Wire</b>
	Wire Type	<b>Stranded</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Housing</b>
Configuration Features	Number of Positions	<b>15</b>
	Number of Rows	<b>5</b>
	Connector Configuration	<b>Drawer</b>
Electrical Characteristics	Operating Voltage	<b>600 VAC [ 600 VDC ]</b>
Contact Features	Contact Type	<b>Socket</b>
Mechanical Attachment	Panel Mount Retention Type	<b>Screw Mount</b>
	Panel Mount Retention	<b>With</b>
Housing Features	Centerline	<b>5.08 mm [ .2 in ]</b>
	Housing Material	<b>Polyester GF</b>
	Housing Color	<b>Black</b>
Dimensions	Length (in)	<b>2.4</b>
	Height (in)	<b>1.208</b>
	Panel Thickness	<b>.031 – .091 in, .8 – 2.3 mm</b>
	Width (in)	<b>2.162</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 130 °C [ -67 – 266 °F ]</b>

---

Operation/Application	For Use With	Receptacle Housing
Industry Standards	UL Rating	<b>Certified, Recognized</b>
	VDE Tested	<b>Yes</b>
	Agency/Standard	<b>CSA, UL</b>
	UL File Number	<b>E28476</b>
	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Quantity	<b>1</b>
	Packaging Method	<b>Package</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

---