



MINI-SAS CAGES



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

MiniSAS HD 1x1 Rec Assy

[MINI-SAS](#) | [MINIPAK HDL](#) , [SAS](#)

2149027-1

TE Internal Number: 2149027-1

Always EU RoHS/ELV Compliant

Number of Ports **1**

Number of Rows **2**

Included Lightpipe **No**

Keyed **No**

Mounting Style **Direct Mount**

Product Drawings

[RECEPTACLE ASSEMBLY, MINI-SASS HD](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[7-1773461-9_MINI_SAS_HD_INTERCONNECT](#)

PDF
English

Product Specifications

Product Specification

[External Mini-SAS HD Connector System](#)

PDF
English

Application Specification

[Mini-SAS HD External Receptacle Connector And Cage Assembly](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_2149027-1_01232013937_dmtec](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[HD Mini-SAS Removal Tools 2161646-1, 2161647-1, 2161648-1](#)

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Included Lightpipe	No
	Shell	With
	PCB Mounting Orientation	Right Angle
	Product Grouping	Mini-SAS HD
	Applies To	Printed Circuit Board
	Connector Type	Mini-SAS HD
	Product Type	Cage, Connector
	Connector Style	Receptacle
Configuration Features	Number of Ports	1
	Number of Rows	2
	Keyed	No
	Number of Positions	36
	Stackable	No
Contact Features	Contact Base Material	Copper Alloy
Termination Features	PCB Termination	Through Hole - Press-Fit
	Termination Post Length	1.64 mm [.065 in]
Mechanical Attachment	Mounting Style	Direct Mount
	PCB Mount Retention	With
	PCB Mount Retention Type	M2 Screws
Housing Features	Housing Color	Black
	Housing Material	LCP (Liquid Crystal Polymer)
Dimensions	Height above PC Board	12.78 mm [.503 in]
	PCB Thickness (Recommended)	.97 mm [.038 in]
Usage Conditions	High Temperature Housing	Yes

Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	72
	Packaging Method	Package, Tray/Box
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

XFP

30 POSN XFP CONN, ENHANCED
1367500-1

Save to List

Find Similar Products

PCI & PCI EXPRESS CONNECTORS

PCI EXPRESS CONN. EON TYPE, 98
1-1871058-3

Save to List

Find Similar Products

I/O CONNECTOR CONTACTS

DYNAMIC D-3 REC CONT L/P 2L
1-917511-3

Save to List

Find Similar Products

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES

03 MODII HDR SRST SHRD LF
5-103414-1

Save to List

Find Similar Products