

2201778-1 Product Details



2201778-1

TE Internal Number: 2201778-1
Active

[View 3D PDF](#)

Removable Memory Products

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- 8 Positions
- Format = Micro Secure Digital Card
- Solder Tab Length = 1.5 mm
- Lead Type = Surface Mount - Inline leads
- Operating Function = Push-On Push-Off

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | [Request Sample](#) | [Find Similar Products](#) | [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [MICRO SD PUSH PUSH LOW PROFILE TYPE \(PDF, English\)](#)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version A\)](#)
- [3D Model \(IGES, Version A\)](#)
- [3D Model \(STEP, Version A\)](#)

[List all Documents](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Mount Angle = Right Angle
- PCB Mount Style = Surface Mount

Mechanical Attachment:

- Mounting Style = Bottom (Printed Circuit Board)

Dimensions:

- Solder Tab Length (mm [in]) = 1.5 [0.059]
- Height off PCB (mm [in]) = 1.65 [0.065]

Body Features:

- Lead Type = Surface Mount - Inline leads
- Shell Material = Copper Alloy

Contact Features:

- Contact Plating, Mating Area, Material = Gold
- Vacuum Tape = With

Housing Features:

- Housing Color = Black
- Housing Material = Thermoplastic

Configuration Features:

- Number of Positions = 8
- Operating Function = Push-On Push-Off

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not reviewed for lead free solder process
- RoHS/ELV Compliance History = Always was RoHS compliant
- UL Flammability Rating = UL 94V-0

Conditions for Usage:

- Format = Micro Secure Digital Card

Packaging Features:

- Packaging Method = Tape & Reel

Other:

- Brand = TE Connectivity

[Investors](#)

[News Room](#)

[Supplier Portal](#)

[Careers](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility](#)

[Plan](#)

[Product Cross Reference](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

[Find a Phone Number](#)

[Knowledge Base](#)

[Manage Your Account](#)

