




COAX CONTACTS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

SUB MIN PIN MULTIMATE

Coaxicon , SB

226537-1

TE Internal Number: 226537-1

Always EU RoHS/ELV Compliant

Applies To **Coaxial Cable, Shielded Wire**

Contact Type **Pin**

Body Style **Straight**

Cable Type **RD 316, RG 161, RG 174, RG 174DB, RG 179, RG 179A, RG 179B, RG 187, RG 187A, RG 187DB, RG 188, RG 188A, RG 316**

Mating Contact Retention **Without**

Product Drawings

[PIN ASSY, SERIES SUBMINIATURE](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[Coaxial Contacts](#)

PDF
English

[AMP Circular Connectors For Commercial Signal & Power Applications](#)

PDF
English

[COAXICON Contacts](#)

PDF
English

[M_SERIES_PIN_AND_SOCKET_CONNECTORS](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[Selection Of Multimate Pin And Socket Contacts](#)

PDF
English



[Selection Of Multimate Pin And Socket Contacts](#)

PDF
Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Applies To	Coaxial Cable, Shielded Wire
	Cable Type	RD 316, RG 161, RG 174, RG 174DB, RG 179, RG 179A, RG 179B, RG 187, RG 187A, RG 187DB, RG 188, RG 188A, RG 316
	Dielectric Material	TPX
	Product Type	Contact
	Connector Type	Coaxial Contacts
Electrical Characteristics	Impedance Options	Non-Matched
Body Features	Body Style	Straight
	Outer Shell Material	Brass
Contact Features	Contact Type	Pin
	Mating Contact Retention	Without
	Center Contact Material	Beryllium Copper
	Contact Mating Area Plating Thickness (µin)	30
Packaging Features	Packaging Method	Carton
Other	Comment	A ferrule is required for each pin and socket., Extraction Tool No. 305183
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

COAX CONTACTS	RF CONNECTOR FERRULES	RECTANGULAR POWER CONNECTORS	POWER CONTACTS
			
SUB MIN SOCKET 51565-1	FERRULE, SUB MIN 1-332056-0	MALE BLOCK 26 P. SER. "M" 201359-1	III+ PIN, 26-24, 15AU/FL, STRIP 66106-7
			

