

## **IDC D-SUB CONNECTORS**







**PRODUCT DRAWING** 



3D PDF

TE CONNECTIVITY (TE)

ASSY, PLUG, 50 POS, B SLOT

CHAMP | Standard CHAMP Products

229974-1

TE Internal Number: 229974-1

Alias ID: 1178449, 1233976, 254182-000, 4-16211-7456, 6635303102, 6635303300, HUB-

Always EU RoHS/ELV Compliant

Connector Style Plug

Solid Wire Range (mm²) .4 - .51

Stranded Wire Range (mm²) .2

Shielded **No** 

Centerline 2.16 mm [.085 in]

**Product Drawings** 

PLUG ASSEMBLY, 50 POSITION, B-SLOT, WITH 4-40 HOLES, CHAMP-LOK

PDF **English** 

**CAD Files** 

Customer View Model

2D\_DXF.ZIP English

3D PDF

PDF **3D** 

**Customer View Model** 

3D\_IGS.ZIP English

Customer View Model

3D STP.ZIP English

**Product Specifications** 

**Product Specification** 

Connector, CHAMP

PDF **English** 

Connector, CHAMP

TIF English

Connector, CHAMP

TIF Japanese

Connector, CHAMP

PDF **Japanese** 

CHAMP Cable Connectors (Standard And Shielded)

PDF **English** 

Qualification Test Report

Application Specification

AMP Standard CHAMP Connector

Japanese

AMP Standard CHAMP Connector

PDF

English

## AMP Standard CHAMP Connector

TIF English

Dl 4	F:	1	1:
Product	Fnvironm	ental Con	nniiance

TE Material Declaration MD\_229974-1\_0729201533\_dmtec

PDF English

Instruction Sheets

Instruction Sheet (U.S.) CHAMP Cable-To-Cable And Cable-To-Panel Connectors

PDF **English** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Plug
	Shielded	No
	Wire/Cable Type	7 Strand, Solid
	Applies To	Cable
	Product Type	Connector
	Product Category	Connectors
	Thread Size	4-40 UNC 2B
	Profile	Standard
	Connector Classification	IDC
	Slot Type Letter Code	В
Configuration Features	Number of Positions	50
Body Features	Color	Black
Contact Features	Contact Mating Area Plating Material	Gold Flash over Palladium Nickel, Gold
	Contact Mating Area Plating Thickness	.76 μm [ 30 μin ]
	Contact Base Material	Copper Alloy
Mechanical Attachment	Flange Thickness	Thick
	Mating Connector Lock	With
	Panel Mount Retention	Without
	Mating Connector Lock Type	Screwlocks

Housing Features	Centerline	2.16 mm [ .085 in ]
	Housing Color Dot Designation	Blue
	Housing Material	Thermoplastic
Dimensions	Solid Wire Range (mm²)	.4 – .51
	Stranded Wire Range (mm²)	.2
	Wire Range (AWG)	24, 26 – 24
	Insulation Diameter (Max)	1.14 mm [ .045 in ]
Packaging Features	Packaging Method	Package, Tray/Box
	Packaging Quantity	100
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE

## **CUSTOMERS ALSO BOUGHT**

