

Ƴ 🖬 f ▼



✓ Active

PRODUCT DRAWING

J 3D PDF

TE CONNECTIVITY (TE) AMPMODU, DBL ROW, CONTACT REC AMPMODU | AMPMODU IV/V

280365

TE Internal Number: 280365

Always EU RoHS/ELV Compliant

Centerline 2.54 mm [.1 in] Number of Positions 8 Number of Rows 2 Row-to-Row Spacing 2.54 mm [.1 in]

Mating Retention With

Product Drawings

AMPMODU II Rec.HSG.Double Row PDF (TIFF AVAILABLE) English

AMPMODU II Rec.HSG.Double Row PDF (TIFF AVAILABLE) English

CAD Files

Customer View Model 3D_IGS.ZIP English

Customer View Model 2D_DXF.ZIP English

Customer View Model 3D_STP.ZIP English

3D PDF PDF English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Style	Receptacle
	Glow Wire Rating	Standard Part - Not Glow Wire
	Connector Type	Housing
	Product Type	Connector
	Applies To	Wire/Cable

Configuration Features	Number of Positions	8
	Number of Rows	2
Contact Features	Contact Layout	Inline
	Contact Type	Socket
Termination Features	Termination Method to Wire/Cable	Crimp
Mechanical Attachment	Mating Retention	With
	Mating Retention Type	Lock
	PCB Mount Retention	With
	Mating Connector Lock	With
	Mating Alignment	With
	Panel Mount Retention	Without
	Mating Connector Lock Type	Detent Latching
	Mating Alignment Type	Latch
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Thermoplastic
	Housing Configuration	Both Ends Closed
	Housing Color	Black
Dimensions	Length (mm)	7.1
	Height	3.1 mm [.12 in]
Industry Standards	UL Flammability Rating	UL 94V-1
Packaging Features	Packaging Quantity	1000
	Packaging Method	Bag
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

