



QUICK DISCONNECTS



TE CONNECTIVITY (TE) FF 375 REC 3-6MM2 TPPB FASTIN-FASTON | 375

280756-4
TE Internal Number: 280756-4

Always EU RoHS/ELV Compliant

Mating Tab Width **9.53 mm [.375 in]**

Mating Tab Thickness **1.22 mm [.048 in]**

Wire Insulation Diameter **3.4 – 5.1 mm [.13 – .201 in]**

Wire Size (AWG) **12 – 10**

Wire Size (mm²) **3 – 6**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[.375 Srs Fastin-Faston Receptacle](#)
PDF (TIFF AVAILABLE)
English

[.375 Srs Fastin-Faston Receptacle](#)
PDF (TIFF AVAILABLE)
English

CAD Files

[Customer View Model](#)
2D_DXF.ZIP
English

[3D PDF](#)
PDF
3D

[Customer View Model](#)
3D_IGS.ZIP
English

[Customer View Model](#)
3D_STP.ZIP
English

Catalog Pages/Data Sheets

[1654742_HOUSEHOLD_APPLIANCES_RAST5](#)
PDF
English

Product Specifications

Product Specification

[FASTIN-FASTON CONN. .110 INCH, .187 INCH, .250 INCH, .375 INCH SRS.](#)
TIF
English

Application Specification

[FASTIN-FASTON CONN. .110 INCH, .187 INCH, .250 INCH, .375 INCH SRS.](#)
PDF
English
[FASTIN FASTON TAB AND RECEPTACLE CONTACT APPLICATION SPECIFICATION](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire Stop	No
	Disconnect Type	Quick Disconnect
	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Type	Regular Wire
	Insulated	No
	Insulated Wire Support	Yes
	Applies To	Wire/Cable

Configuration Features	Paired	No
	Stud Hole	No
	Terminal Angle	Straight
	Connection Capacity	Single

Electrical Characteristics	Voltage (Max) (V)	250
----------------------------	-------------------	------------

Body Features	Plating Material	Phosphor Bronze, Tin
	Fully Insulated	Yes

Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin

Termination Features	Crimp Type	F-Crimp
----------------------	------------	----------------

Mechanical Attachment	Mating Retention Type	Locking Lance
	Locking Lance Height (mm)	1.25

Dimensions	Mating Tab Width	9.53 mm [.375 in]
	Mating Tab Thickness	1.22 mm [.048 in]
	Wire Insulation Diameter	3.4 – 5.1 mm [.13 – .201 in]
	Wire Size (AWG)	12 – 10
	Wire Size (mm ²)	3 – 6
	Material Thickness	.51 mm [.02 in]
	Overall Length	29 mm [1.14 in]

Usage Conditions	Operating Temperature Range (°C)	-30 – 105
Operation/Application	For Housing Type	Single or Multiple
Packaging Features	Packaging Method	Reel
	Packaging Quantity	2000
Other	Comment	According to DIN 46340, Part 4


Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

RELAY SOCKETS




VCF7-1000=FROM SEC
VCF7-1000

[Save to List](#)

[Find Similar Products](#)

THROUGH-HOLE RESISTORS




YR1 0.1% 267K
YR1B267KCC

[Save to List](#)

[Find Similar Products](#)

WIRE-TO-BOARD CONNECTOR CONTACTS




POSITIVE LOCK RECP
170234-1

[Save to List](#)

[Find Similar Products](#)

TERMINATORS



STOP-REAR
690674-1

[Save to List](#)

[Find Similar Products](#)

Products - 2 Results


[View All](#) [Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Toolings
Tooling

[See All Toolings](#)

	<p>PRODUCT - TOOLINGS</p>	<input checked="" type="checkbox"/>
	<p>Application Tooling - OCEAN Applicators AMP</p> <p>OC-AT-S-FA-160F250F-001-0065 - 2150374-2</p> <p>TE INTERNAL NUMBER: 2150374-2</p> <p>✓ Active</p>	<p>Not in Scope for EU RoHS/ELV Compliance</p> <p>Region Worldwide</p> <p>Tool Type Applicator</p> <p>Spare Parts Tooling No</p>

Spare Parts Tooling **Yes**

Applicator Style **OCEAN -
Atlantic**

Applicator Feed Style **Side Feed**

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

**OC-160F250F-
CRIMPTOOLINGKIT
- 7-2150374-7**

TE INTERNAL NUMBER: 7-2150374-7

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **Yes**

Spare Parts Tool Type **Spare
Parts Kit**

