Our commitment. Your advantage.

Search

**Live Product Chat** 

Check Pricing & Availability

Contact Us About This Product

My Account

**Products** 

**Documentation** 

Resources

**My Account** 

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# **ROX2SJ22K Product Details**



ROX2SJ22K

(3-1625890-2)

TE Internal Number: 3-1625890-2



#### **Fixed Resistors**

Converted to EU RoHS/ELV Compliant (Statement of Compliance)

### **Product Highlights:**

- Resistor Type = Power Resistor
- Resistance Selection = K?
- Resistance = 22K?
- Power Rating = 2.00 W
- Tolerance = 5 %

View all Features









**Quick Links** 

Search for Tooling Product Feature Selector

#### **Documentation & Additional Information**

### **Product Drawings:**

None Available

## Catalog Pages/Data Sheets:

• Flame Proof Power Metal Oxide Film Resistors - Type ... (PDF, English)

### **Product Specifications:**

None Available

## **Application Specifications:**

None Available

### **Instruction Sheets:**

• None Available

## **CAD Files:**

None Available

# **Additional Information:**

• Product Line Information

#### **Related Products:**

• Tooling

List all Documents

## Product Features (Please use the Product Drawing for all design activity)

### **Product Type Features:**

- Resistor Type = Power Resistor
- Resistance (?) = 22K
- Element = Metal Oxide
- <u>Termination Type</u> = Tinned Copper Leads

### **Electrical Characteristics:**

- Resistance Selection (?) = K
- Power Rating (W) = 2.00
- Tolerance (%) = 5
- <u>Package Type</u> = Ammo Packed

### **Body Related Features:**

- <u>Series</u> = ROX
- Mount Style = Axial Leaded
- Package, Component Size = 11 x 4.0

# **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

### **Conditions for Usage:**

• Temperature Coefficient (ppm/?C) = ?300

## Operation/Application:

• Application = Power

### Other:

• Brand = Neohm