



# PCB D-SUB CONNECTORS



TE CONNECTIVITY (TE)

## 15w D skt W B/L & 4-40 s/lock 15u" gold

AMPLIMITE | Solder Cup Connectors

3-1634223-2

TE Internal Number: 3-1634223-2

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline (mm) **2.77**

Number of Positions **15**

Number of Rows **2**

Shell Size **2**

Active

PRODUCT DRAWING  
English

3D PDF

### Product Drawings

D-SUB HD20, VERTICAL, 15P SKT CONNECTOR

PDF  
English

### CAD Files

3D PDF

PDF  
3D

Customer View Model

2D\_DXF.ZIP  
English

Customer View Model

3D\_IGS.ZIP  
English

Customer View Model

3D\_STP.ZIP  
English

### Product Environmental Compliance

TE Material Declaration

MD\_3-1634223-2\_062620141018\_dmtec

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Connector Style

**Receptacle**

Shell Size

**2**

PCB Mounting Orientation

**Vertical**

Grounding Straps

**With**





Shell Type

**Full Metal Shell**

	Grounding Indents	<b>Without</b>
	Applies To	<b>Printed Circuit Board</b>
	Sealed	<b>No</b>
	Product Type	<b>Connector</b>
<hr/>		
Configuration Features	Number of Positions	<b>15</b>
	Number of Rows	<b>2</b>
	Preloaded	<b>Yes</b>
<hr/>		
Body Features	Plastic	<b>No</b>
	Color Code	<b>None</b>
	Shell Plating Material	<b>Nickel</b>
	Color	<b>Black</b>
	Shell Material	<b>Steel</b>
	Post Size (mm)	<b>.6</b>
<hr/>		
Contact Features	Solder Tail Contact Plating Material	<b>Tin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µin)	<b>15</b>
	Contact Mating Area Plating Material	<b>Gold</b>
<hr/>		
Termination Features	Termination Post Length	<b>5.2 mm [ .204 in ]</b>
	Grounding Clips	<b>Without</b>
<hr/>		
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Boardlocks</b>
	Mating Connector Lock	<b>With</b>
	Mating Connector Lock Type	<b>Female Screwlocks, 4-40 UNC</b>
	Panel Mount Retention	<b>Without</b>
	Mating Retention Type	<b>Screw</b>
	Boardlock Material	<b>Brass</b>
	Mating Retention	<b>With</b>
	PCB Mount Alignment	<b>With</b>
	Mounting Hole Diameter (mm)	<b>3.1</b>
	Boardlock Plating Material	<b>Nickel</b>

Housing Features	Centerline (mm)	<b>2.77</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>
Dimensions	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>UL E28476</b>
Packaging Features	Packaging Method	<b>Tray</b>
	Packaging Quantity	<b>70</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

TOGGLE SWITCHES	SURFACE MOUNT RESISTORS	PCB D-SUB CONNECTORS	PCB D-SUB CONNECTORS
 <p><b>A105T1ZQ04</b> 4-1825137-1</p>	 <p><b>TLR 2512 1.0W R033 1% 75PPM 2K RL</b> TLR3A10WR033FTDG</p>	 <p><b>25w D plg W B/L &amp; 4-40 s/lock 15u" gold</b> 3-1634220-2</p>	 <p><b>9w D skt W B/L &amp; 4-40 s/lock 15u" gold</b> 3-1634222-2</p>
<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>