



QUICK DISCONNECTS



✓ Active

[↓](#) **PRODUCT DRAWING**
English

[↓](#) **3D PDF**



TE CONNECTIVITY (TE)

250 ULTRA-FAST RCPT 16-14 TPBR

[Ultra-Fast](#) | 250

3-350819-2

TE Internal Number: 3-350819-2

Alias ID: 1062346, 402682769

[Always EU RoHS/ELV Compliant](#)

Mating Tab Width **6.35 mm [.25 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter (Max) **4.06 mm [.16 in]**

Wire Size (AWG) **16 – 14**

Wire Size (mm²) **1.31 – 2.08**

Product Drawings

[RECEPTACLE ASSY,ULTRA-FAST, .250 SERIES,16-14 AWG](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

Product Specifications

Product Specification

[Ultra-Fast Fully Insulated FASTON Receptacle Terminals](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_3-350819-2_05282015346_dmtec](#)

PDF
English


Product Type Features	Wire Stop	Yes
	Disconnect Type	Quick Disconnect Pin
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Wire/Cable Type	Discrete Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Terminal Angle	Straight
Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Tin
	Fully Insulated	Yes
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter (Max)	4.06 mm [.16 in]
	Wire Size (AWG)	16 – 14
	Wire Size (mm²)	1.31 – 2.08
	Overall Length	21.755 mm [.855 in]
Usage Conditions	Operating Temperature Range (°C)	105
Industry Standards	UL Rating	Listed
	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Reel

OtherBarrel ColorBlue

Product ComplianceStatement of CompliancePDFVIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

CHASSIS PANEL MOUNT RESISTORS




THS75 2R2 5%
THS752R2J

Save to List

Find Similar Products

CRIMP QUICK DISCONNECTS




250 ULTRA-FAST TAB 16-14 TPBR
3-520106-2

Save to List

Find Similar Products

CRIMP QUICK DISCONNECTS




RECEPT, PIDG FASTON 16-14 205
640913-2

Save to List

Find Similar Products

CRIMP QUICK DISCONNECTS



FF 187 REC 22-16AWG BR
62802-1

Save to List


Find Similar Products

Products - 2 ResultsView AllCompare 0/10

Relation Type

RELATIONSHIPToolingsToolingSee All Toolings

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators AMP

OC-AT-S-FA-205D-001-0086 - 2151032-2

TE INTERNAL NUMBER: 2151032-2

Active

Not in Scope for EU RoHS/ELV Compliance

Region Worldwide

Tool Type Applicator

Spare Parts Tooling No

Applicator Style OCEAN - Atlantic

Applicator Feed Style Side Feed

✓

RELATIONSHIPToolingsToolingSee All Toolings



PRODUCT - TOOLINGS

Application Tooling - OCEAN Applicators
AMP

OC-205D-
CRIMPTOOLINGKIT
- 7-2151032-7

TE INTERNAL NUMBER: 7-2151032-7

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **Yes**

Spare Parts Tool Type **Spare
Parts Kit**

