



HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

06P MTA100 CONN ASSY 22AWG RED

MTA | MTA-100

3-640440-6

TE Internal Number: 3-640440-6
 Alias ID: 1419493

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **6**

Number of Rows **1**

Contact Mating Area Plating Material **Tin**

Contact Mating Area Plating Material Finish **Matte**

✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

Product Drawings

[MTA 100 CONNECTOR ASSEMBLY, 22 AWG, STANDARD](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

Catalog Pages/Data Sheets

[MTA, CST-100 II, SL-156 And AMP Economy Power \(EP\) Connectors](#)

PDF
English

Product Specifications

Product Specification

[Connector, MTA-100](#)

PDF
English

Application Specification

[MTA 100 Connector](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Connector Type	Connector Assembly
	Connector System	Wire-to-Post
	Wire/Cable Type	Discrete Wire, Stranded
	Strain Relief	With
	Sealed	No
	Connector Style	Receptacle
	Applies To	Wire/Cable
	Connector Design	Closed End
<hr/>		
Configuration Features	Number of Positions	6
	Number of Rows	1
	Backwall/Post Interruptions	Without
<hr/>		
Electrical Characteristics	Operating Voltage (VAC)	250
<hr/>		
Body Features	Cable Exit Angle	90°
<hr/>		
Contact Features	Contact Mating Area Plating Material	Tin
	Contact Mating Area Plating Material Finish	Matte
	Contact Mating Area Plating Thickness	2.03 μm [80 μin]
	Underplate Material	Nickel
	Contact Termination Area Plating Thickness	2.03 – 5.08 μm [80 – 200 μin]
	Underplate Material Thickness	.762 μm, 30 μin
	Contact Termination Area Plating Material	Tin
	Contact Type	Socket
	Contact Current Rating (A)	5
	Contact Layout	Inline
	Contact Termination Area Plating Material Finish	Matte
	Contact Base Material	Copper Alloy
<hr/>		
Termination Features	Termination Method to Wire/Cable	IDC
<hr/>		
Mechanical Attachment	PCB Mount Alignment	Without
	Mating Retention	With
	PCB Mount Retention	Without
	Contact Retention	With
	Contact Retention Type	Locking Latches





	Contact Retention Type	Locking Lance
	Mating Retention Type	Locking Ramp
	Panel Mount Retention	Without
	Mating Alignment	Without
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Red
	Housing Style	Standard
	Housing Material	Nylon
<hr/>		
Dimensions	Height	6.99 mm [.275 in]
	Wire/Cable Size (AWG)	22
	Wire/Cable Size (mm ²)	.3 – .4
	Insulation Diameter	1.52 mm [.06 in]
	Length	15.24 mm [.6 in]
<hr/>		
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
<hr/>		
Operation/Application	For Use With	MTA .100 Headers & MTA .100 IDC Posted Connectors
	Pick and Place Cover	Without
<hr/>		
Industry Standards	UL Flammability Rating	UL 94V-2
	UL File Number	E28476
	CSA Rating	Certified
	Agency/Standard	CSA, UL
	CSA File Number	LR7189
	UL Rating	Recognized
<hr/>		
Packaging Features	Packaging Method	Bag/Box
	Packaging Quantity	500
<hr/>		
Other	Comment	Stripe may run down between ribs
<hr/>		

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>12P MTA100 CONN ASSY 22AWG RED 4-640440-2</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>10 MTE HDR SRRAL LTCH.100CL LF 5-103635-9</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD HEADERS & RECEPTACLES</p>  <p>08P MTA100 CONN ASSY 22AWG RED 3-640440-8</p> <p>Save to List Find Similar Products</p>	<p>WIRE-TO-BOARD CONNECTOR HOUSINGS</p>  <p>AMP UNIVERSAL POWER CAP 6P 176285-1</p> <p>Save to List Find Similar Products</p>
---	---	---	--

Products - 36 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)


	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - W-T-B Headers & Receptacles MTA MTA-100</p> <p>06P MTA100 HI-TEMP HDR SN TL - 3-647295-6 TE INTERNAL NUMBER: 3-647295-6</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Centerline 2.54 mm</p> <p>Number of Positions 6</p> <p>PCB Mounting Orientation Vertical</p> <p>PCB Mounting Style Through Hole</p> <p>Number of Rows 1</p>	<input checked="" type="checkbox"/>
---	---	---	-------------------------------------

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - W-T-B Headers & Receptacles MTA MTA-100</p> <p>06P MTA100 HDR ASSY F/L HITEMP - 3-647050-6 TE INTERNAL NUMBER: 3-647050-6</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Centerline 2.54 mm</p> <p>Number of Positions 6</p> <p>PCB Mounting Orientation Vertical</p> <p>PCB Mounting Style Through Hole</p> <p>Number of Rows 1</p>	<input checked="" type="checkbox"/>
---	---	---	-------------------------------------

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - W-T-B Headers & Receptacles
MTA | MTA-100

06P MTA100 PSTD

CONN ASSY LF

- 3-647003-6

TE INTERNAL NUMBER: 3-647003-6

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

Number of Positions **6**

Number of Rows **1**

Contact Mating Area Plating

Material **Tin**

Contact Mating Area Plating

Material Finish **Matte**