



## HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

### 03P MTA100 HDR ASSY (NARROW)

[MTA](#) | [MTA-100](#)

3-644456-3

TE Internal Number: 3-644456-3

[Always EU RoHS/ELV Compliant](#)

Centerline **2.54 mm [ .1 in ]**

Number of Positions **3**

PCB Mounting Orientation **Vertical**

PCB Mounting Style **Through Hole**

Number of Rows **1**

✓ Active

[↓ PRODUCT DRAWING](#)  
English

[↓ 3D PDF](#)

#### Product Drawings

[MTA-100 HEADER ASSEMBLY,NARROW, .025 SQUARE STRAIGHT POST, TIN PLATED](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[MTA, CST-100 II, SL-156 And AMP Economy Power \(EP\) Connectors](#)

PDF  
English

#### Product Specifications

Product Specification

[Connector, MTA-100](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_3-644456-3\\_05222015250\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	PCB Mounting Orientation	<b>Vertical</b>
	Product Type	<b>Connector</b>
	Connector Type	<b>Header</b>
	Connector System	<b>Wire-to-Board</b>
	Strain Relief	<b>Without</b>
	Sealed	<b>No</b>
	Connector Style	<b>Plug</b>
	Applies To	<b>Printed Circuit Board</b>

---

Configuration Features	Number of Positions	<b>3</b>
	Number of Rows	<b>1</b>
	Backwall/Post Interruptions	<b>Without</b>

---

Electrical Characteristics	Operating Voltage (VAC)	<b>250</b>
----------------------------	-------------------------	------------

---

Body Features	Header Type	<b>Breakaway</b>
---------------	-------------	------------------

---

Contact Features	Contact Mating Area Plating Material	<b>Tin</b>
	Contact Mating Area Plating Thickness	<b>3.81 – 8.89 µm [ 150 – 350 µin ]</b>
	Underplate Material	<b>Nickel</b>
	Contact Termination Area Plating Thickness	<b>3.81 – 8.89 µm [ 150 – 350 µin ]</b>
	Underplate Material Thickness	<b>1.27 µm, 50 µin</b>
	Contact Style	<b>Straight</b>
	Contact Shape	<b>Square</b>
	Tail Plating Material	<b>Tin</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Tail Plating Thickness	<b>3.81 – 8.89 µm [ 150 – 350 µin ]</b>
	Contact Type	<b>Pin</b>
	Contact Current Rating (A)	<b>5</b>
	Contact Layout	<b>Inline</b>
	Contact Termination Area Plating Material Finish	<b>Matte</b>
	Contact Base Material	<b>Copper Alloy</b>

---

Termination Features	Termination Method to PC Board	<b>Through Hole - Solder</b>
	Termination Method to Wire/Cable	<b>Solder</b>

Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>Without</b>
	PCB Mount Retention	<b>Without</b>
	Contact Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment	<b>Without</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Natural</b>
	Housing Style	<b>Narrow</b>
	Housing Material	<b>Polyester - GF</b>
Dimensions	Tail Length	<b>2.79 mm [ .11 in ]</b>
	Mating Post Length	<b>7.49 mm [ .295 in ]</b>
	PCB Thickness (Recommended)	<b>1.6 mm [ .063 in ]</b>
	Height	<b>10.03 mm [ .395 in ]</b>
	Length	<b>7.32 mm [ .288 in ]</b>
Usage Conditions	Operating Temperature Range	<b>-55 – 105 °C [ -67 – 221 °F ]</b>
Operation/Application	For Use With	<b>MTA .100 Connector Assembly</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	UL File Number	<b>E28476</b>
	CSA Rating	<b>Certified</b>
	Agency/Standard	<b>CSA, UL</b>
	CSA File Number	<b>LR7189</b>
	UL Rating	<b>Recognized</b>
Packaging Features	Packaging Method	<b>Bag/Box</b>
	Packaging Quantity	<b>500</b>
Other	Comment	<b>Mates with CST-100 connector</b>

Products - 73 Results

[View All](#)

Compare 0/10



Relation Type



RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles  
MTA | MTA-100**03P MTA100 CONN  
ASSY LF - 3-641537-3**

TE INTERNAL NUMBER: 3-641537-3

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**Number of Positions **3**Number of Rows **1**

Contact Mating Area Plating

Material **Tin**

Contact Mating Area Plating

Material Finish **Matte**

RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles  
MTA | MTA-100**03P MTA100 CONN  
ASSY POL TAB  
- 644083-3**

TE INTERNAL NUMBER: 644083-3

✓ Active

Not EU RoHS or ELV Compliant

Centerline **2.54 mm**Number of Positions **3**Number of Rows **1**

Contact Mating Area Plating

Material **Tin-Lead**

Contact Mating Area Plating

Material Finish **Bright**

RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS

Connectors - W-T-B Headers & Receptacles  
MTA | MTA-100**03P MTA100 CONN  
ASSY GRN LF**

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**Number of Positions **3**



- 3-640623-3

TE INTERNAL NUMBER: 3-640623-3

✓ Active

Number of Rows **1**

Contact Mating Area Plating

Material **Tin**

Contact Mating Area Plating

Material Finish **Matte**