




HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)

05P MTA100 HDR ASSY (NARROW)

MTA | MTA-100

3-644456-5

TE Internal Number: 3-644456-5

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **5**

PCB Mounting Orientation **Vertical**

PCB Mounting Style **Through Hole**

Number of Rows **1**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[MTA-100 HEADER ASSEMBLY,NARROW, .025 SQUARE STRAIGHT POST, TIN PLATED](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

Catalog Pages/Data Sheets

[MTA, CST-100 II, SL-156 And AMP Economy Power \(EP\) Connectors](#)

PDF
English

Product Specifications

Product Specification

[Connector, MTA-100](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_3-644456-5_05222015146_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Product Type	Connector
	Connector Type	Header
	Connector System	Wire-to-Board
	Strain Relief	Without
	Sealed	No
	Connector Style	Plug
	Applies To	Printed Circuit Board

Configuration Features	Number of Positions	5
	Number of Rows	1
	Backwall/Post Interruptions	Without

Electrical Characteristics	Operating Voltage (VAC)	250
----------------------------	-------------------------	------------

Body Features	Header Type	Breakaway
---------------	-------------	------------------

Contact Features	Contact Mating Area Plating Material	Tin
	Contact Mating Area Plating Thickness	3.81 – 8.89 µm [150 – 350 µin]
	Underplate Material	Nickel
	Contact Termination Area Plating Thickness	3.81 – 8.89 µm [150 – 350 µin]
	Underplate Material Thickness	1.27 µm, 50 µin
	Contact Style	Straight
	Contact Shape	Square
	Tail Plating Material	Tin
	Contact Termination Area Plating Material	Tin
	Tail Plating Thickness	3.81 – 8.89 µm [150 – 350 µin]
	Contact Type	Pin
	Contact Current Rating (A)	5
	Contact Layout	Inline
	Contact Termination Area Plating Material Finish	Matte
	Contact Base Material	Copper Alloy

Termination Features	Termination Method to PC Board	Through Hole - Solder
	Termination Method to Wire/Cable	Solder

Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Alignment	Without
	Mating Retention	Without
	PCB Mount Retention	Without
	Contact Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Natural
	Housing Style	Narrow
	Housing Material	Polyester - GF
Dimensions	Tail Length	2.79 mm [.11 in]
	Mating Post Length	7.49 mm [.295 in]
	PCB Thickness (Recommended)	1.6 mm [.063 in]
	Height	10.03 mm [.395 in]
	Length	12.4 mm [.488 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	MTA .100 Connector Assembly
Industry Standards	UL Flammability Rating	UL 94V-0
	UL File Number	E28476
	CSA Rating	Certified
	Agency/Standard	CSA, UL
	CSA File Number	LR7189
	UL Rating	Recognized
Packaging Features	Packaging Method	Bag/Box
	Packaging Quantity	500
Other	Comment	Mates with CST-100 connector

PDF

[VIEW ALL PRODUCT COMPLIANCE](#)