



STANDARD RECTANGULAR CONNECTORS



TE CONNECTIVITY (TE)

DYNAMIC 3500 HDR ASSY 20P V

[Dynamic Series](#) | [Dynamic 3000 Series](#)

316517-2

TE Internal Number: 316517-2

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type **Polarization**

Mating Retention **Without**

PCB Mount Retention **With**

✓ Active

↓ **PRODUCT DRAWING**
Japanese

↓ **3D PDF**

Product Drawings

[DYNAMIC \(D-3500\) 20 POS. V HDR. ASS'Y](#)

PDF (**TIFF AVAILABLE**)

Japanese

[DYNAMIC \(D-3500\) 20 POS. V HDR. ASS'Y](#)

PDF (**TIFF AVAILABLE**)

Japanese

CAD Files

[Customer View Model](#)

2D_DXF.ZIP

English

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

English

[3D PDF](#)

PDF

English

Catalog Pages/Data Sheets

[D3000 Series Dynamic Connectors Continued](#)

PDF

English

[1-1773732-4_DYNAMIC_SERIES_CATALOG_ENGLISH](#)

PDF

English

Product Specifications

Product Specification

[Dynamic Connector D-3000 Series](#)

TIF

Japanese

[Dynamic Connector D-3000 Series](#)

PDF

Japanese

Qualification Test Report

[DYNAMIC D-3000 SERIES CONNECTOR](#)

PDF

Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Connector
	PCB Mounting Orientation	Vertical
	Sealed	No
	Connector System	Wire-to-Board
	Shielded	No
	Insertion Force	High
	Row-to-Row Spacing	5.08 mm [.2 in]
	Connector Style	Plug
	Glow Wire Rating	Standard Part - Not Glow Wire
	Strain Relief	Without
	Series Number	3000
	Shrouded	Yes
	Connector Type	Header
	Applies To	Printed Circuit Board

Configuration Features	Number of Positions	20
	Number of Rows	2
	Preloaded	Yes
	Selectively Loaded	No

Electrical Characteristics	Operating Voltage	600 VAC [600 VDC]
	UL Voltage Rating	250 VAC [250 VDC]

Body Features	Header Type	Shrouded
	Sealable	No

Contact Features	Contact Plating Material	Gold
	Contact Current Rating (A)	15
	Tail Plating Thickness	2 μm [78.74 μin]
	Multiple Contact Types	Without
	Contact Style	Straight
	Contact Type	Tab
	Tail Plating Material	Tin

	Termination Method to PC Board	Through Hole - Solder
Mechanical Attachment	Mating Alignment	With
	Mating Alignment Type	Polarization
	Mating Retention	Without
	PCB Mount Retention	With
	PCB Mount Retention Type	Retention Leg
	Contact Retention	Without
	PCB Mount Alignment	Without
Housing Features	Centerline	5.08 mm [.2 in]
	Housing Material	Polyester GF
	Housing Color	Black
Dimensions	PCB Thickness (Recommended)	1.6 mm [.063 in]
	Tail Length	3.8 mm [.149 in]
	Height	21.6 mm [.85 in]
	Width	18.17 mm [.715 in]
	Length	52.8 mm [2.07 in]
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	Receptacle Housing
	Assembly Integration Feature	Without
	Halogen Free	Yes
Industry Standards	UL Flammability Rating	UL 94V-0
	CSA File Number	LR7189
	VDE Tested	No
	CSA Rating	Certified
	UL Rating	Recognized
	Agency/Standard	CSA, UL

Packaging Features

Packaging Quantity

9

Packaging Method











Tube, Tube/Box

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

RECTANGULAR CONNECTOR HOUSINGS	OCEAN APPLICATORS	STANDARD RECTANGULAR CONNECTORS	STANDARD RECTANGULAR CONNECTORS
			
<p>DYNAMIC 1500T REC HSG 6P X BLACK 1-2069029-2</p>	<p>CRIMPER, WIRE SPECIAL 1-234156-1</p>	<p>DYNAMIC 3500 HDR ASSY 12P V 316516-2</p>	<p>DYNAMIC D2100 HDR V ASSY 12P 1318126-1</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>