



CRIMP RINGS & SPADES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) TERMINAL, SOLIS R 8 8 SOLISTRAND | SOLISTRAND

324061
 TE Internal Number: 324061
 Mil-Spec: MS20659-140
 Alias ID: AMP-0-0324061-0, CN5237-000

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **4.34 mm [.171 in]**

Sealed **No**

Heavy Duty **No**

Wire Size (AWG) **8**

Product Drawings

TERMINAL, RING TONGUE, SOLISTRAND

PDF
English

CAD Files

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

3D PDF

PDF
3D

Product Environmental Compliance

TE Material Declaration

MD_324061_0522201472_dmtec

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Sealed	No
Barrel Type	Closed Barrel
Wire/Cable Type	Regular Wire
Insulated	No
Insulated Wire Support	No

Stud Size	8, M4
Shape Code	RING-049
Wire/Cable Composition	Solid or Stranded

Configuration Features	Terminal Angle	Straight
	Number of Holes	1

Body Features	Plating Material	Copper, Tin
	Inspection Slot	No
	Weight per Piece (g)	2.99

Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight
	Class	2

Dimensions	Stud Diameter	4.34 mm [.171 in]
	Wire Size (AWG)	8
	Wire Size (mm ²)	6.64 – 10.5
	Wire Size (CMA)	13100 – 20800
	Barrel Inside Diameter	4.37 mm [.172 in]
	Material Thickness (mm)	1.22
	Overall Length	24.1 mm [.9488 in]
	Barrel Inside Diameter (Min)	4.37 mm [.172 in]

Usage Conditions	High Temperature Rating	170 °C [338 °F]
	Operating Temperature Range (°C)	170

Operation/Application	Heavy Duty	No
-----------------------	------------	-----------













Industry Standards	Government Qualified	Yes
--------------------	----------------------	------------

Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	100

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP RINGS & SPADES	RECTANGULAR POWER CONNECTORS	N TYPE COAX CONNECTORS	TO-5/.100 GRID RELAYS
			
<p>TERMINAL, SOLIS FLAG R 12-10 36272</p>	<p>24P MINI UMNL PLUG HSG 770587-1</p>	<p>N BHSkt 50Ohm Silver Pltd 1-1337417-0</p>	<p>J1MAP-26XM = M39016/7- 024M J1MAP-26XM</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>