



Base Material:


Annealed Copper — (ASTM B-188)
Electrodeposited Tin Plate —
(MIL-T-10727)




B




C'



E



F'



I'

Terminals


Wire Size	Wire Range	Barrel I.D. Min.	Tongue Thickness Max.	Style	Stud Size	Dimensions					Part Numbers
						L Max.	H Max.	C Min.	K	W Max.	
250 MCM 127 mm ²	231-275 MCM	.690 17.53	.15 3.81	B	3/8	2.58 65.53	.63 16.00	.62 15.75	—	1.28 32.51	325703
				B	1/2 M12	2.58 65.53	.63 16.00	.62 15.75	—	1.28 32.51	325705
				B	3/8	2.69 68.33	.63 16.00	.62 15.75	—	1.40 35.56	325803
				B	1/2 M12	2.69 68.33	.63 16.00	.62 15.75	—	1.40 35.56	325805
300 MCM 152 mm ²	275-325 MCM	.758 19.25	.16 4.06	B	5/8	2.82 71.63	.63 16.00	.75 19.05	—	1.40 35.56	325807
				C	3/8	3.70 93.98	.63 16.00	.62 15.75	1.00 25.40	1.40 35.56	326805
				C	3/8	3.70 93.98	.63 16.00	.62 15.75	1.00 25.40	1.40 35.56	326805-1*
				C	1/2 M12	4.43 112.52	.63 16.00	.62 15.75	1.75 44.45	1.40 35.56	327286
350 MCM 177mm ²	325-375 MCM	.819 20.80	.17 4.32	B	3/8	2.79 70.87	.63 16.00	.62 15.75	—	1.51 38.35	325903
				B	1/2 M12	2.79 70.87	.63 16.00	.62 15.75	—	1.51 38.35	325905
				C	3/8	3.79 96.27	.63 16.00	.62 15.75	1.00 25.40	1.51 38.35	326806
				C	1/2 M12	4.55 115.57	.63 16.00	.62 15.75	1.75 44.45	1.51 38.35	327287
400MCM 203mm ²	375-450 MCM	.876 22.25	.18 4.57	C	1/2	4.55 115.57	.63 16.00	.62 15.75	1.75 44.45	1.51 38.35	327287-3
				B	1/2 M12	2.89 73.41	.63 16.00	.62 15.75	—	1.61 40.89	326005
				C	3/8	3.90 99.06	.63 16.00	.62 15.75	1.00 25.40	1.61 40.89	326807
				B	3/8	3.29 83.57	.76 19.30	.75 19.05	—	1.80 45.72	326103
500MCM 253mm ²	450-550 MCM	.981 24.92	.20 5.08	B	1/2 M12	3.29 83.57	.76 19.30	.75 19.05	—	1.80 45.72	326105
				C	1/2 M12	4.80 121.92	.61 15.49	.62 15.75	1.75 44.45	1.80 45.72	327289
				C	3/8	4.05 102.87	.63 16.00	.62 15.75	1.00 25.40	1.80 45.72	326808
				I	1/2 M12	5.88 149.35	.63 16.00	.62 15.75	1.75 44.45	1.80 45.72	53642-2
600MCM 304mm ²	550-650 MCM	1.075 27.31	.22 5.59	F	3/8	4.22 107.19	.63 16.00	.62 15.75	1.00 25.40	1.95 49.53	326809-1* ²
800MCM 405mm ²	750-850 MCM	1.242 31.55	.25 6.35	E	1/2	3.72 94.49	.76 19.30	.75 19.05	—	2.26 57.40	326405 ²

* No sight hole.


¹ Per NEMA specifications

² Two crimps necessary.

Special Terminals



Slotted Stud Hole



Centerline 2-Hole

Wire Size	Wire Range	Stud Size	Barrel I.D. Min.	Tongue Thickness Max.	Dimensions					Part Numbers
					L Max.	H Max.	C Min.	K	W Max.	
Slotted Stud Hole										
400 MCM	375-450 MCM	3/8	.876 22.25	.18 4.57	5.82 147.83	.44 11.18	3.29 83.57	1.30 33.02	1.61 40.89	276963-1
500 MCM	450-550 MCM	3/8	.981 24.92	.20 5.08	6.01 6.35	.44 11.18	3.25 82.55	1.30 33.02	1.80 45.72	276964-1
Centerline 2-Hole										
444.4 MCM	444.4 MCM	3/8	.991 25.17	.26 6.60	4.01 101.85	.45 11.43	2.00 50.80	1.00 25.40	1.26 32.00	326151-1

For complete product information, order Catalog 82025