



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

03P UMNL PLUG HSG UL94V0

MATE-N-LOK | Universal MATE-N-LOK

350766-4

TE Internal Number: 350766-4

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **3**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[PLUG, 3 CIRCUIT, UNIVERSAL MATE-N-LOK\(TM\)](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

PDF
English

Product Specifications

Product Specification

[Universal MATE-N-LOK Connector](#)

PDF
English

Application Specification

[Universal MATE-N-LOK Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_350766-4_05052015458_dmtec](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[Universal MATE-N-LOK Connectors](#)

Universal, Commercial, And .140 MATE-N-LOK Contact And Housing Selection Charts

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Plug
	Contact Type	Pin or Socket

Configuration Features	Number of Positions	3
	Centerline	6.35 mm [.25 in]
	Number of Rows	1
	Contact Layout	Inline
	Multiple Contact Types	Without

Electrical Characteristics	Operating Voltage (VAC)	600
----------------------------	-------------------------	------------

Contact Features	Contact Retention	Without
------------------	-------------------	----------------

Mechanical Attachment	Assembly Integration Feature	Without
-----------------------	------------------------------	----------------

Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	White
	Housing Material	Nylon GF

Usage Conditions	Sealed Condition	Not Sealed
------------------	------------------	-------------------

Operation/Application	Connector System	Wire-to-Wire
	Applies To	Wire/Cable
	Operating Temperature	-55 – 125 °C [-67 – 257 °F]

Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	UL Rating	Recognized
	VDE Tested	Yes
	CSA Rating	Certified

CSA File Number	LR16455
Agency/Standard Number	E28476
Agency/Standard	CSA, UL

Packaging Features	Packaging Method	Bag
	Packaging Quantity	500





Other	For Use With	Appropriate Universal MATE-N-LOK Cap or Header
-------	--------------	---

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

POWER CONTACTS	POWER CONTACTS	RECTANGULAR POWER CONNECTORS	BUS BAR CONNECTORS
			
UNIV.M-N-L.PIN 926894-3	UNIVERSAL M-N-L PIN 926883-1	03P UMNL CAP HSG V0 350767-1	CROWN CLIP JUNIOR SCREW-MOUNT CONN 1982995-1
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products

Products - 149 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - Power Contacts
MATE-N-LOK | Universal MATE-N-LOK

UMNL SPLIT PIN
AUNI/BR - 350687-7
TE INTERNAL NUMBER: 350687-7

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **19 A**

Operating Voltage **600 VAC**

Wire/Cable Size **20 - 14 AWG**




RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - Power Contacts
MATE-N-LOK | Universal MATE-N-LOK

UNIV.M-N-L.SOCKET
- 926884-1

TE INTERNAL NUMBER: 926884-1

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **19 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **24 – 18 AWG**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - Power Contacts
MATE-N-LOK | Universal MATE-N-LOK

UMNL SOK 24-18 PTPBR
- 350851-1

TE INTERNAL NUMBER: 350851-1
ALIAS ID: 0-0350851-1, 2021755, AMPS-0-0350851-1,
CU3086-000

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **19 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **24 – 18 AWG**

