



RECTANGULAR POWER CONNECTORS



✓ Active

[PRODUCT DRAWING](#)
English

[3D PDF](#)



TE CONNECTIVITY (TE)

03P UMNL CAP HSG V0

[MATE-N-LOK](#) | [Universal MATE-N-LOK](#)

350767-1

TE Internal Number: 350767-1

Alias ID: AMP-0-0350767-1, F84278-000

[Always EU RoHS/ELV Compliant](#)

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Panel, Wire-to-Wire**

Applies To **Panel, Wire/Cable**

Number of Positions **3**

Product Drawings

[CAP,3 CIRCUIT, UNIVERSAL MATE-N-LOK](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

PDF
English

Product Specifications

Product Specification

[Universal MATE-N-LOK Connector](#)

PDF
English

Application Specification

[Universal MATE-N-LOK Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_350767-1_08082014245_dmtec](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[Universal MATE-N-LOK Connectors](#)

Universal, Commercial, And .140 MATE-N-LOK Contact And Housing Selection
Charts


Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Receptacle
	Contact Type	Pin or Socket
Configuration Features	Number of Positions	3
	Centerline	6.35 mm [.25 in]
	Number of Rows	1
	Contact Layout	Inline
	Multiple Contact Types	Without
Electrical Characteristics	Operating Voltage (VDC)	600
Contact Features	Contact Retention	Without
Mechanical Attachment	Panel Mount Retention Type	Patch & Tabs
	Panel Mount Retention	With
	Assembly Integration Feature	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Natural
	Housing Material	Nylon GF
Dimensions	Panel Thickness	.76 – 2.29 mm [.03 – .09 in]
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Panel, Wire-to-Wire
	Applies To	Panel, Wire/Cable
	Operating Temperature	-55 – 125 °C [-67 – 257 °F]

Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	UL Rating	Recognized
	VDE Tested	Yes
	CSA Rating	Certified
	CSA File Number	LR7189
	Agency/Standard Number	E28476
	Agency/Standard	CSA, UL
Packaging Features	Packaging Method	Package
	Packaging Quantity	1
Other	For Use With	Appropriate Universal MATE-N-LOK Plug
Product Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

THROUGH-HOLE RESISTORS




LR1 1% 30K
LR1F30K

Save to List

Find Similar Products

RECTANGULAR POWER CONNECTORS




03P UMNL PLUG HSG
350766-1

Save to List

Find Similar Products

RECTANGULAR POWER CONNECTORS




03P UMNL PLUG HSG
UL94V0
350766-4

Save to List

Find Similar Products

STREET LIGHTING PHOTO CONTROLS



ALR-AM-1-A-NB
385640-000

Save to List

Find Similar Products

Products - 151 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS	✓
---------------------------	---



Connectors - Rectangular Power Connectors
MATE-N-LOK | Universal MATE-N-LOK

03P UMNL PLUG TEST
ASSY 94VO - 350848-3

TE INTERNAL NUMBER: 350848-3

✓ Active

Always EU RoHS/ELV Compliant

Housing Type **Plug**

Connector System **Wire-to-Wire**

Applies To **Wire/Cable**

Contact Current Rating **5 A**

Number of Positions **3**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - Power Contacts
MATE-N-LOK | Universal MATE-N-LOK

UNIV-MNL SPLIT ST
- 926898-6

TE INTERNAL NUMBER: 926898-6

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **19 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **20 – 14 AWG**




RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - Power Contacts
MATE-N-LOK | Universal MATE-N-LOK

UMNL PIN 20-14
AU/NI/BR - 350538-2

TE INTERNAL NUMBER: 350538-2

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **19 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **20 – 14 AWG**

