



BOARD-TO-BOARD JUMPERS & SHUNTS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

SHUNT, ECON, PHBR15 AU, BLUE

AMP

382811-2

TE Internal Number: 382811-2

Always EU RoHS/ELV Compliant

Shunt Type **Economy**

Shunt Style **Open Top**

Centerline **2.54 mm [.1 in]**

Number of Positions **2**

Product Drawings

ECONOMY SHUNT ASSEMBLY

PDF
English

CAD Files

3D PDF

PDF
English

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

AMPMODU_INTERCONNECTION_SYSTEM_SECTION_6_7AND8

PDF
English

Product Environmental Compliance

TE Material Declaration

MD_382811-2_04232011612

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

Low Profile, Economy, And Dual Beam Shunt Connectors 382811, 390088, And 382823

PDF
English

Low Profile, Economy, And Dual Beam Shunt Connectors 382811, 390088, And 382823

TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Profile	Low
	Product Type	Shunt

Configuration Features	Number of Positions	2
------------------------	---------------------	----------

Electrical Characteristics	Insulation Resistance (MΩ)	1000
----------------------------	----------------------------	-------------

Body Features	Handle	Without
---------------	--------	----------------

Contact Features	Shunt Type	Economy
	Shunt Style	Open Top
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness	.381 μm [15 μin]
	Contact Mating Area Plating Material	Gold

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	Polyester - GF
	Housing Color	Blue

Dimensions	Height	6.35 mm [.25 in]
------------	--------	---------------------------

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
------------------	----------------------------------	------------------

Industry Standards	UL Rating	Recognized
	CSA Certified	Yes
	UL Flammability Rating	UL 94V-0

Packaging Features	Packaging Method	Box
	Packaging Quantity	1500

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

