Our commitment. Your advantage.

Search

**Live Product Chat** 

Check Pricing & Availability

Contact Us About This Product

**Product Feature Selector** 

Search for Tooling

**Quick Links** 

**Products** 

**Documentation** 

Resources

My Account

**Customer Support** 

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>Resistors</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# **ROX2SJ3K9 Product Details**



ROX2SJ3K9 (4-1625890-8)TE Internal Number: 4-1625890-8 <u>Active</u>

#### **Fixed Resistors**

Converted to EU RoHS/ELV Compliant (Statement of Compliance)


### **Product Highlights:**

- Resistor Type = Power Resistor
- Resistance Selection = K?
- Resistance = 3.9K ?
- Power Rating = 2.00 W
- Tolerance = 5 %

View all Features



🕒 Add to My Part List 🕡





## **Documentation & Additional Information**

## **Product Drawings:**

None Available

#### Catalog Pages/Data Sheets:

• Flame Proof Power Metal Oxide Film Resistors - Type ... (PDF, English)

### **Product Specifications:**

None Available

#### **Application Specifications:**

None Available

## **Instruction Sheets:**

None Available

## **CAD Files:**

None Available

# **Additional Information:**

• Product Line Information

#### **Related Products:**

Tooling

**List all Documents** 

# Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- Resistor Type = Power Resistor
- <u>Resistance (?)</u> = 3.9K
- <u>Element</u> = Metal Oxide
- <u>Termination Type</u> = Tinned Copper Leads

## **Electrical Characteristics:**

- Resistance Selection (?) = K
- Power Rating (W) = 2.00
- Tolerance (%) = 5
- Package Type = Ammo Packed

## **Body Related Features:**

- <u>Series</u> = ROX
- Mount Style = Axial Leaded
- <u>Package, Component Size</u> = 11 x 4.0

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240?C, Wave solder capable to 260?C, Wave solder capable to 265?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

## **Conditions for Usage:**

• Temperature Coefficient (ppm/?C) = ?300

## **Operation/Application:**

## Other:

• Brand = Neohm