



# RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

## 10P MTA156 CONN ASSY 18AWG ORA

MTA | MTA156

4-640426-0

TE Internal Number: 4-640426-0

Always EU RoHS/ELV Compliant

Product Type **Connector Assembly**

Housing Type **Receptacle**

Connector System **Wire-to-Post**

Applies To **Wire/Cable**

Contact Current Rating (A) **7**

Active

PRODUCT DRAWING  
English

3D PDF

### Product Drawings

[MTA 156 CONNECTOR ASSEMBLY, 18 AWG, STANDARD](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

[MTA, CST-100 II, SL-156 And AMP Economy Power \(EP\) Connectors](#)

PDF  
English

### Product Specifications

Product Specification

[System, Connector/Header, MTA 156](#)

PDF  
English

Application Specification

[MTA 156 Connectors](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Housing Type	<b>Receptacle</b>
	Contact Type	<b>Socket</b>
Configuration Features	Number of Positions	<b>10</b>
	Centerline	<b>3.96 mm [ .156 in ]</b>
	Number of Rows	<b>1</b>
	Contact Layout	<b>Inline</b>
Electrical Characteristics	Contact Current Rating (A)	<b>7</b>
	Operating Voltage (VAC)	<b>600</b>
Contact Features	Contact Retention	<b>With</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Contact Mating Area Plating Material	<b>Tin</b>
	Contact Mating Area Plating Thickness	<b>2.03 – 5.08 µm [ 80 – 200 µin ]</b>
	Contact Base Material	<b>Copper Alloy</b>
	Contact Mating Area Plating Material Finish	<b>Matte</b>
	Underplate Material Thickness	<b>.762 µm [ 30 µin ]</b>
	Contact Termination Area Plating Thickness	<b>2.03 – 5.08 µm [ 80 – 200 µin ]</b>
	Underplate Material	<b>Nickel</b>
	Contact Retention Type	<b>Locking Lance</b>
Termination Features	Wire/Cable Size (AWG)	<b>18</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.8 – .9</b>
	Termination Method to Wire/Cable	<b>Insulation Displacement Crimp (IDC)</b>
	Wire Type	<b>Stranded</b>
	Wire/Cable Type	<b>Discrete Wire</b>
Mechanical Attachment	Mating Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>Without</b>
	PCB Mount Alignment	<b>Without</b>
	Mating Retention Type	<b>Locking Ramp</b>
	Panel Mount Retention	<b>Without</b>
	Strain Relief	<b>With</b>
Housing Features	UL Flammability Rating	<b>UL 94V-2</b>

Housing Color	<b>White</b>
Housing Material	<b>Nylon</b>
Cable Exit Angle	<b>90°</b>
Housing Style	<b>Standard Profile</b>
Wire/Cable Installation Type	<b>Closed End</b>

Dimensions	Accepts Wire Insulation Diameter Range	<b>2.41 mm [ .095 in ]</b>
	Height	<b>9.02 mm [ .355 in ]</b>
	Length	<b>39.62 mm [ 1.56 in ]</b>

Usage Conditions	Sealed Condition	<b>Not Sealed</b>
------------------	------------------	-------------------

Operation/Application	Connector System	<b>Wire-to-Post</b>
	Applies To	<b>Wire/Cable</b>
	Operating Temperature	<b>-55 – 105 °C [ -67 – 221 °F ]</b>

Industry Standards	CSA Rating	<b>Certified</b>
	Agency/Standard Number	<b>E28476</b>
	UL Rating	<b>Recognized</b>
	CSA File Number	<b>LR7189</b>
	Agency/Standard	<b>CSA, UL</b>

Packaging Features	Packaging Method	<b>Bag/Box</b>
	Packaging Quantity	<b>250</b>

Other	Backwall/Post Interruptions	<b>Without</b>
	For Use With	<b>MTA .156 Header</b>

Product Compliance [Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

<p><b>RECTANGULAR POWER CONNECTORS</b></p> 	<p><b>RECTANGULAR POWER CONNECTORS</b></p> 	<p><b>CRIMP RINGS &amp; SPADES</b></p> 	<p><b>PCB CONNECTOR COVERS</b></p> 
--	--	--	--

<p>10P MTA156 CONN ASSY 18AWG ORA 4-640431-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>10P MTA156 CONN ASSY 18AWG ORA 4-640599-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>PIDG R 22-16 COMM 22-18 MIL 8 31888</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>06P MTA156 COVER 640551-6</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
--	--	--	--

Products - 16 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)


	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - W-T-B Headers &amp; Receptacles MTA   MTA156</p> <p><b>10P MTA156 HDR ASSY STR RND SN - 1-644750-0</b></p> <p>TE INTERNAL NUMBER: 1-644750-0</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Centerline <b>3.96 mm</b></p> <p>Number of Positions <b>10</b></p> <p>PCB Mounting Orientation <b>Vertical</b></p> <p>PCB Mounting Style <b>Through Hole</b></p> <p>Number of Rows <b>1</b></p>	<input checked="" type="checkbox"/>
--	---	--	-------------------------------------

RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - W-T-B Headers &amp; Receptacles MTA   MTA156</p> <p><b>10P MTA156 HDR ASSY STR SQ SN - 1-644749-0</b></p> <p>TE INTERNAL NUMBER: 1-644749-0</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Centerline <b>3.96 mm</b></p> <p>Number of Positions <b>10</b></p> <p>PCB Mounting Orientation <b>Vertical</b></p> <p>PCB Mounting Style <b>Through Hole</b></p> <p>Number of Rows <b>1</b></p>	<input checked="" type="checkbox"/>
---	--	--	-------------------------------------

RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors  
MTA | MTA156

## 10P MTA156 HDR ASSY SQ STR F/L - 1-644752-0

TE INTERNAL NUMBER: 1-644752-0

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Header**

Housing Type **Plug**

Connector System **Wire-to-Board**

Applies To **Printed Circuit Board**

Contact Current Rating **7 A**

