




QUICK DISCONNECTS



TE CONNECTIVITY (TE)

.250 FAST REC IS 22-18 BR

FASTON | 250

41771

TE Internal Number: 41771

Always EU RoHS/ELV Compliant

Mating Tab Width **6.35 mm [.25 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter **2.29 – 3.3 mm [.09 – .13 in]**

Wire Size (AWG) **22 – 18**

Wire Size (mm²) **.3 – .8**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[RECEPTACLE, FASTON, 6.35 \[.250\] SERIES](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

Catalog Pages/Data Sheets

[82004 FASTON Terminals \(Insulated And Uninsulated\) Catalog - FASTON Receptacles Section](#)

PDF
English

Product Specifications

Application Specification

[FASTON CONN. .250 SR. REC CTC & LIF REC CTC](#)

PDF
English

[FASTON Straight Receptacles With "F-" Crimp Feature](#)

PDF
English

[Wire Preparation And Crimp Inspection Guide](#)

PDF
English

[Wire Preparation And Crimp Inspection Guide](#)

TIF
English

Product Environmental Compliance

TE Material Declaration

[MD_41771_091820141022_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Insulated	No
	Support Style	Insulation Support
	Applies To	Wire/Cable

Configuration Features	Paired	No
	Terminal Angle	Straight
	Connection Capacity	Single

Body Features	Plating Material	Brass, Unplated
	Fully Insulated	No

Contact Features	Terminal Orientation	Straight
------------------	----------------------	-----------------

Termination Features	Crimp Type	F-Crimp
----------------------	------------	----------------

Mechanical Attachment	Mating Retention Type	Dimple
-----------------------	-----------------------	---------------

Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter	2.29 – 3.3 mm [.09 – .13 in]
	Wire Size (AWG)	22 – 18
	Wire Size (mm ²)	.3 – .8
	Material Thickness	.41 mm [.016 in]
	Overall Length	19.18 mm [.755 in]

Operation/Application	For Housing Type	Single
-----------------------	------------------	---------------

Industry Standards	UL Rating	Listed
--------------------	-----------	---------------

CSA Certified

Yes

Packaging Features

Packaging Method

Reel

Packaging Quantity

12500

Other

Line





Premier

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

I/O CONNECTOR CONTACTS	CRIMP RINGS & SPADES	CRIMP QUICK DISCONNECTS	CRIMP RINGS & SPADES
 <p>RCPT 250 POS-LOCK 22-18 0126BR 1217378-1</p> <p>Save to List</p> <p>Find Similar Products</p>	 <p>RING IS 22-18 10 020BR 42036-2</p> <p>Save to List</p> <p>Find Similar Products</p>	 <p>250 FLAG FAST RCPI 22-16 016BR 63577-1</p> <p>Save to List</p> <p>Find Similar Products</p>	 <p>RING IS 18-14 10 .020TPBR 41333</p> <p>Save to List</p> <p>Find Similar Products</p>