



## QUICK DISCONNECTS



TE CONNECTIVITY (TE)

### FF 250 TAB 18-16AWG BR

FASTIN-FASTON | 250

42241-1

TE Internal Number: 42241-1

Always EU RoHS/ELV Compliant

Mating Tab Width **6.35 mm [ .25 in ]**

Mating Tab Thickness **.81 mm [ .032 in ]**

Wire Insulation Diameter (Max) (mm) **4.06**

Wire Insulation Diameter **3.05 – 4.06 mm [ .12 – .16 in ]**

Wire Size (AWG) **18 – 14**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

#### Product Drawings

[TAB, FASTIN-FASTON, 6.35 \[.250\] SERIES](#)

PDF  
English

#### CAD Files

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[1654742\\_HOUSEHOLD\\_APPLIANCES\\_RAST5](#)

PDF  
English

#### Instruction Sheets

Instruction Sheet (non U.S.)

[AMP DOUBLE ACTION HAND TOOL 720725-1](#)

PDF  
Japanese













[AMP DOUBLE ACTION HAND TOOL 720725-1](#)

PDF  
Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	FASTON	<b>Yes</b>
	Wire/Cable Type	<b>Regular Wire</b>
	Insulated Wire Support	<b>Yes</b>
	Applies To	<b>Wire/Cable</b>
Configuration Features	Paired	<b>No</b>
	Terminal Angle	<b>Straight</b>
	Connection Capacity	<b>Single</b>
Body Features	Plating Material	<b>Brass, Unplated</b>
	Fully Insulated	<b>No</b>
Contact Features	Underplating Material	<b>Brass</b>
	Terminal Orientation	<b>Straight</b>
	Contact Plating Material	<b>Unplated</b>
Termination Features	Crimp Type	<b>F-Crimp</b>
Mechanical Attachment	Mating Retention Type	<b>Locking Lance</b>
	Locking Lance Height	<b>1.4 mm [ .055 in ]</b>
Dimensions	Mating Tab Width	<b>6.35 mm [ .25 in ]</b>
	Mating Tab Thickness	<b>.81 mm [ .032 in ]</b>
	Wire Insulation Diameter (Max) (mm)	<b>4.06</b>
	Wire Insulation Diameter	<b>3.05 – 4.06 mm [ .12 – .16 in ]</b>
	Wire Size (AWG)	<b>18 – 14</b>
	Wire Size (mm <sup>2</sup> )	<b>.8 – 2</b>
	Material Thickness	<b>.38 mm [ .015 in ]</b>
	Overall Length	<b>29.18 mm [ 1.149 in ]</b>
Operation/Application	For Housing Type	<b>Multiple</b>
Packaging Features	Packaging Method	<b>Loose Piece</b>
	Packaging Quantity	<b>500</b>
Other	Comment	<b>Without Locking Hole</b>

## CUSTOMERS ALSO BOUGHT

AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS	MOTOR TERMINAL HOUSINGS	MOTOR TERMINAL HOUSINGS	SOLDERSLEEVE SHIELD TERMINATORS
			
<p><b>070 MLC W-W CAP HSG 8P NATURAL</b> 174931-1</p>	<p><b>FASTON REC HSG 2P PBT NAT</b> 928673-1</p>	<p><b>FF 250 TAB HSG 3P NYLON NAT</b> 926097-1</p>	<p><b>CWT-3807</b> 5-1193606-3</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>