



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

.250 FAST REC IS 18-14 BR

FASTON | 250

42400-1

TE Internal Number: 42400-1

Always EU RoHS/ELV Compliant

Mating Tab Width **6.35 mm [.25 in]**

Mating Tab Thickness **.81 mm [.032 in]**

Wire Insulation Diameter **3.05 – 4.32 mm [.12 – .17 in]**

Wire Size (AWG) **18 – 14**

Wire Size (mm²) **.8 – 2**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[RECEPTACLE, FASTON, .250 SERIES](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

Catalog Pages/Data Sheets

[82004 FASTON Terminals \(Insulated And Uninsulated\) Catalog - FASTON Receptacles Section](#)

PDF
English

Product Specifications

Application Specification

[FASTON Straight Receptacles With "F-" Crimp Feature](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_42400-1_121620152114_dmtec](#)

PDF
English

Product Type Features	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Insulated	No
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Terminal Angle	Straight
	Connection Capacity	Single
Body Features	Plating Material	Brass, Unplated
	Fully Insulated	No
Contact Features	Underplating Material	Brass
	Terminal Orientation	Straight
Termination Features	Crimp Type	F-Crimp
Mechanical Attachment	Mating Retention Type	Dimple
Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
	Wire Insulation Diameter	3.05 – 4.32 mm [.12 – .17 in]
	Wire Size (AWG)	18 – 14
	Wire Size (mm ²)	.8 – 2
	Material Thickness	.39 mm [.0157 in]
	Overall Length	19.05 mm [.75 in]
Industry Standards	UL Rating	Listed
	CSA Certified	Yes
Packaging Features	Packaging Method	Reel
	Packaging Quantity	10000

Other

Line





Budget

Product Compliance

Statement of Compliance
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	MOTOR TERMINAL HOUSINGS	RECTANGULAR POWER CONNECTORS	CRIMP QUICK DISCONNECTS
			
187 FAST REC 18-14 014BR 62016-1	FASTON 250 REC HSG NYLON NAT 1-480416-0	4P S/R FH PLUG VAL-U- LOK V2 1586024-4	250 FLAG FAST RCPT 18- 12 016BR 42511-1
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products

Products - 3 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)


PRODUCT - TOOLINGS		
	Application Tooling - OCEAN Applicators AMP OC-110F180F- CRIMPTOOLINGKIT - 7-2150016-7 TE INTERNAL NUMBER: 7-2150016-7 ✓ Active	Not in Scope for EU RoHS/ELV Compliance Region Worldwide Tool Type Applicator Spare Parts Tooling Yes Spare Parts Tool Type Spare Parts Kit

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS		
	Application Tooling - OCEAN Applicators AMP	Not in Scope for EU RoHS/ELV



AMP
**OC-AT-E-FA-110F180F-
001-0056 - 2150016-2**
TE INTERNAL NUMBER: 2150016-2

✓ Active

Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **No**

Applicator Style **OCEAN -
Atlantic**

Applicator Feed Style **End Feed**

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

**OC-AT-E-FM-110F180F-
001-0056 - 2150016-1**
TE INTERNAL NUMBER: 2150016-1

✓ Active

**Not in Scope for EU RoHS/ELV
Compliance**

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **No**

Applicator Style **OCEAN -
Atlantic**

Applicator Feed Style **End Feed**

