



MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

08 MODII HDR SRRA SHRD .100CL

AMPMODU | AMPMODU Headers

5-102523-6

TE Internal Number: 5-102523-6

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **8**

Header Type **Shrouded**

Product Drawings

[HEDADER ASSEMBLY MOD II, SINGLE ROW .100 C/L, RIGHT ANGLE](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[AMPMODU_INTERCONNECTION_SYSTEM_SECTIONS](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Right Angle

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

	Stabilizers	Without
	Strain Relief	Without
	Board Standoff	With
	Profile	Standard
	Product Type	Connector
	Gasket	Without
<hr/>		
Configuration Features	Number of Positions	8
	Number of Rows	1
	Keyed	No
	Selectively Loaded	No
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	750 Vrms
<hr/>		
Body Features	Header Type	Shrouded
	Post Size	.64 mm [.025 in]
<hr/>		
Contact Features	Contact Protection	With
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	100 – 200
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Mating Area Plating Material	Tin-Lead
	Contact Protection Type	Shrouded
	Contact Current Rating (A)	3
<hr/>		
Termination Features	Termination Post Length	2.79 mm [.11 in]
	Termination End Plating Thickness (µin)	100 – 200
	Termination End Plating Material	Tin Over Nickel
	Termination Method to PC Board	Through Hole
<hr/>		
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	With

Mating Connector Lock	Without
Mating Alignment Type	Polarization

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
	Housing Style	4-Sided

Dimensions	Shrouded End Dimension	1.778 mm [.07 in]
	PCB Thickness (Recommended)	1.397 mm [.055 in]
	Mating Post Length	6.1 mm [.24 in]

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Housing	No

Operation/Application	High Speed Serial Data Connector	No
-----------------------	----------------------------------	-----------

Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, UL E28476


Packaging Features	Packaging Quantity	23
	Packaging Method	Tube

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES</p>  <p>07 MODII HDR SRRA SHRD LF 5-103361-5</p> <p>Save to List Find Similar Products</p>	<p>MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES</p>  <p>10 MODII HDR SRRA SHRD LF 5-103361-8</p> <p>Save to List Find Similar Products</p>	<p>I/O CONNECTOR CONTACTS</p>  <p>HE/HA-C-STI.AU.0, 5 1-1105100-2</p> <p>Save to List Find Similar Products</p>	<p>MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES</p>  <p>10 MODII HDR DRRA SHRD LF 5-102617-3</p> <p>Save to List Find Similar Products</p>
---	---	--	---

Products - 1 Results

[View All](#)

[Compare 0/10](#)

Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS		<input checked="" type="checkbox"/>
	<p>Connectors - FFC Connectors FFC FFC</p> <p>008 HOUSING FFC RCPT 100CL SR - 487769-6</p> <p>TE INTERNAL NUMBER: 487769-6</p> <p> Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Connector Type Housing</p> <p>Connector Style Receptacle</p> <p>Centerline 2.54 mm</p> <p>Number of Positions 8</p> <p>Number of Rows 1</p>