



## HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### 08 MTE HDR SRRA LATCH.100CL LF

[AMPMODU](#) | [AMPMODU MTE](#)

5-103634-7

TE Internal Number: 5-103634-7

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

Number of Positions **8**

PCB Mounting Orientation **Right Angle**

PCB Mounting Style **Through Hole**

Number of Rows **1**

#### Product Drawings

[HEADER ASSEMBLY, RIGHT ANGLE, SINGLE ROW, 2.54 \[.100\] C/L 0.64 \[.025\] SQ POST, WITH PLZN & LATCHING, AMPMODU MTE](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

#### Catalog Pages/Data Sheets

[AMPMODU\\_INTERCONNECTION\\_SYSTEM\\_SECTION5\\_CONT](#)

PDF  
English

[AMPMODU MTE INTERCONNECT SYSTEM](#)

PDF  
English

#### Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	<b>Right Angle</b>
	Product Type	<b>Connector</b>
	Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
	Connector Type	<b>Header</b>
	Strain Relief	<b>Without</b>
	Connector Style	<b>Plug</b>
	PCB Orientation Feature	<b>No</b>
	Applies To	<b>Printed Circuit Board</b>
Configuration Features	Number of Positions	<b>8</b>
	Number of Rows	<b>1</b>
	Backwall/Post Interruptions	<b>Without</b>
Electrical Characteristics	Dielectric Withstanding Voltage	<b>600 V</b>
	Termination Resistance	<b>15 M<math>\Omega</math></b>
	Insulation Resistance	<b>5000 M<math>\Omega</math></b>
Body Features	Header Type	<b>Shrouded</b>
Contact Features	Contact Mating Area Plating Material	<b>Tin</b>
	Contact Mating Area Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Contact Type	<b>Pin</b>
	Solder Tail Contact Plating Material	<b>Tin</b>
	Contact Termination Area Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Tail Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Contact Current Rating (A)	<b>3</b>
	Contact Shape	<b>Square</b>
	Tail Plating Material	<b>Tin</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Contact Termination Area Plating Material Finish	<b>Matte</b>
	Contact Base Material	<b>Brass</b>
Termination Features	Termination Method to Wire/Cable	<b>Crimp, Insulation Displacement Crimp (IDC)</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>With</b>

	Mating Retention	.....
	PCB Mount Retention	<b>Without</b>
	Contact Retention	<b>With</b>
	Mating Alignment Type	<b>Latched</b>
	Contact Retention Type	<b>Locking Lance</b>
	Mating Alignment	<b>With</b>
	Mating Retention Type	<b>Polarized Lock</b>
<hr/>		
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>
<hr/>		
Dimensions	Tail Length	<b>3.3 mm [ .13 in ]</b>
	Mating Post Length	<b>5.84 mm [ .23 in ]</b>
	Length	<b>22.86 mm [ .9 in ]</b>
	Height	<b>13.59 mm [ .535 in ]</b>
<hr/>		
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
<hr/>		
Operation/Application	For Use With	<b>Receptacle Housing Assembly</b>
	Pick and Place Cover	<b>Without</b>
<hr/>		
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
<hr/>		
Packaging Features	Packaging Method	<b>Tube, Tube/Box</b>
	Packaging Quantity	<b>23</b>
<hr/>		
Other	Comment	<b>Use Keying Tool No. 91417-1 to remove post for keying.</b>
<hr/>		
Product Compliance	<a href="#">Statement of Compliance PDF</a> <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

<a href="#">WIRE-TO-BOARD HEADERS &amp; RECEPTACLES</a>	<a href="#">ROTARY SWITCHES</a>	<a href="#">RIBBON CABLE CONNECTORS</a>	<a href="#">MOTOR TERMINALS</a>
---	---------------------------------	---	---------------------------------



06 MTE HDR SRRA  
LATCH.100CL LF  
5-103634-5



Save to List



Find Similar Products



DRD10CE04=ROT DIP, 10P  
1825007-1



Save to List



Find Similar Products



MICRO-MATCH FEM.SE  
215460-8



Save to List



Find Similar Products



PC TAB STANDARD  
SIAMEZE  
4-1601009-4



Save to List



Find Similar Products



Products - 1 Results

View All

Compare 0/10



Relation Type



RELATIONSHIP

## Mating Products

Used to identify Mating Parts

See All Mating Products

PRODUCT - MATING PRODUCTS



Connectors - FFC Connectors  
FFC | FFC

008 HOUSING FFC RCPT  
100CL SR - 487526-7

TE INTERNAL NUMBER: 487526-7

✓ Active

Always EU RoHS/ELV Compliant

Connector Type **Housing**

Connector Style **Receptacle**

Centerline **2.54 mm**

Number of Positions **8**

Number of Rows **1**