



## HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### 08 MTE HDR SRRA LTCH.100CL LF

[AMPMODU](#) | [AMPMODU MTE](#)

5-103635-7

TE Internal Number: 5-103635-7

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

Termination Method to Wire/Cable **Crimp, Insulation Displacement Crimp (IDC)**

Number of Positions **8**

PCB Mounting Orientation **Right Angle**

PCB Mounting Style **Through Hole**

#### Product Drawings

[HDR ASSY, RTANG, SINGLE ROW 2.54\[.100\] C/L , 0.64\[.025\] SQ POST, WITH PLZN & LATCHING, AMPMODU MTE](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[AMPMODU\\_INTERCONNECTION\\_SYSTEM\\_SECTION5\\_CONT](#)

PDF  
English

[AMPMODU MTE INTERCONNECT SYSTEM](#)

PDF  
English

#### Product Specifications

Application Specification

[AMPMODU MTE Interconnection System](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_5-103635-7\\_07072014239\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	PCB Mounting Orientation	<b>Right Angle</b>
	Product Type	<b>Connector</b>
	Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
	Connector Type	<b>Header</b>
	Strain Relief	<b>Without</b>
	Connector Style	<b>Plug</b>
	PCB Orientation Feature	<b>No</b>
	Applies To	<b>Printed Circuit Board</b>

---

Configuration Features	Number of Positions	<b>8</b>
	Number of Rows	<b>1</b>
	Backwall/Post Interruptions	<b>Without</b>

---

Electrical Characteristics	Dielectric Withstanding Voltage	<b>600 V</b>
	Termination Resistance	<b>15 M<math>\Omega</math></b>
	Insulation Resistance	<b>5000 M<math>\Omega</math></b>

---

Body Features	Header Type	<b>Shrouded</b>
---------------	-------------	-----------------

---

Contact Features	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Mating Area Plating Thickness ( $\mu$ in)	<b>15</b>
	Contact Type	<b>Pin</b>
	Solder Tail Contact Plating Material	<b>Tin</b>
	Contact Termination Area Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Tail Plating Thickness	<b>2.54 <math>\mu</math>m [ 100 <math>\mu</math>in ]</b>
	Contact Current Rating (A)	<b>3</b>
	Contact Shape	<b>Square</b>
	Tail Plating Material	<b>Tin</b>
	Contact Termination Area Plating Material	<b>Tin</b>
	Contact Termination Area Plating Material Finish	<b>Matte</b>
	Contact Base Material	<b>Brass</b>

---

Termination Features	Termination Method to Wire/Cable	<b>Crimp, Insulation Displacement Crimp (IDC)</b>
----------------------	----------------------------------	---





Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Alignment	<b>Without</b>
	Mating Retention	<b>With</b>
	PCB Mount Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Contact Retention	<b>With</b>
	Mating Alignment Type	<b>Latched</b>
	Contact Retention Type	<b>Locking Lance</b>
	Mating Alignment	<b>With</b>
Mating Retention Type	<b>Polarized Lock</b>	
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>
Dimensions	Tail Length	<b>3.3 mm [ .13 in ]</b>
	Mating Post Length	<b>5.84 mm [ .23 in ]</b>
	Length	<b>22.86 mm [ .9 in ]</b>
	Height	<b>13.59 mm [ .535 in ]</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
Operation/Application	For Use With	<b>Receptacle Housing Assembly</b>
	Pick and Place Cover	<b>Without</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
Packaging Features	Packaging Method	<b>Tube, Tube/Box</b>
	Packaging Quantity	<b>23</b>
Other	Comment	<b>Use Keying Tool No. 91417-1 to remove post for keying.</b>

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

<p>WIRE-TO-BOARD CONNECTOR HOUSINGS</p>  <p>2X8 MTE RCPT SR LATCH .100CL 5-103957-7</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>FFC CONNECTORS</p>  <p>008 HOUSING FFC RCPT 100CL SR 487378-7</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>FFC CONNECTORS</p>  <p>004 HOUSING FFC RCPT 100CL SR 487378-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p>WIRE-TO-BOARD HEADERS &amp; RECEPTACLES</p>  <p>04 MTE HDR SRRA LTCH.100CL LF 5-103635-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
--	---	---	--

Products - 1 Results

[View All](#)

Compare 0/10 [↔](#)

Relation Type ▼

RELATIONSHIP

### Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - FFC Connectors

### 008 HOUSING FFC RCPT 100CL SR

FFC | FFC

487526-7

TE INTERNAL NUMBER: 487526-7

✓ Active

Always EU RoHS/ELV Compliant

Connector Type **Housing**

Connector Style **Receptacle**

Centerline **2.54 mm**

Number of Positions **8**

Number of Rows **1**

[Product Drawing](#)

[3D PDF](#)

