

✓ Active

[↓](#) **PRODUCT DRAWING**  
English

[↓](#) **3D PDF**

TE CONNECTIVITY (TE)

## 2X9 MTE RCPT SR LATCH & POL

[AMPMODU](#) | [AMPMODU MTE](#)

5-103958-8

TE Internal Number: 5-103958-8

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

Number of Positions **9**

Number of Rows **1**

Row-to-Row Spacing **2.54 mm [ .1 in ]**

Mating Retention **With**

### Product Drawings

**RCPT ASSY, AMPMODU MTE, SINGLE ROW, .100 C/L, LATCHED & POLARIZED,  
FOR NO 22-NO 26 AWG WIRE SIZE, STRIP FORM**

PDF  
English

### CAD Files

**Customer View Model**

2D\_DXF.ZIP  
English

**Customer View Model**

3D\_IGS.ZIP  
English

**Customer View Model**

3D\_STP.ZIP  
English

**3D PDF**

PDF  
English

### Catalog Pages/Data Sheets

**AMPMODU\_INTERCONNECTION\_SYSTEM\_SECTION5\_CONT**

PDF  
English

**AMP MODU MTE Section Of Catalog 1307819**

PDF  
English

**AMPMODU MTE INTERCONNECT SYSTEM**

PDF  
English

### Product Specifications

Application Specification

**AMPMODU MTE Interconnection System**

PDF  
English


Drawing for an assembly only.

Product Type Features	Row-to-Row Spacing	2.54 mm [ .1 in ]
	Glow Wire Rating	Standard Part - Not Glow Wire
	Applied Pressure	Standard
	Connector Type	Housing
	Applies To	Wire/Cable
	Connector Style	Receptacle
	Strain Relief	With
	Product Type	Connector
Configuration Features	Number of Positions	9
	Number of Rows	1
Electrical Characteristics	Dielectric Withstanding Voltage	600 VAC
	Operating Voltage	267 V
	Termination Resistance	15 mΩ
	Insulation Resistance (MΩ)	5000
Contact Features	Contact Type	Socket
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin
	Contact Current Rating (A)	3
	Contact Layout	Inline
Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
Mechanical Attachment	Mating Retention	With
	Mating Retention Type	Latch
	PCB Mount Retention	Without
	Mating Connector Lock	With
	Panel Mount Retention	Without
	Mating Connector Lock Type	Latch
	Mating Alignment	With
	Lock Type	Latch
	Mating Alignment Type	Latch

Housing Features	Centerline	2.54 mm [ .1 in ]
	Housing Color	Black
	Housing Material	Thermoplastic
Dimensions	Height	5.08 mm [ .2 in ]
	Insulation Diameter	1.37 mm [ .054 in ]
	Length	45.72 mm [ 1.8 in ]
	Wire/Cable Size (AWG)	26 – 22
	Wire/Cable Size (mm²)	.12 – .4
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	Mates with Headers
Industry Standards	Approved Standards	CSA LR7189, UL E28476
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	24
	Packaging Method	Tube
Other	Comment	Maximum insulation diameter is 1.14 [.045] for Pneumatic Terminators., Ribbon Cable Notched handles 22-28 AWG
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

PCB TERMINALS




FASTON 250 PCB TAB  
TPBR  
1217126-1

Save to List

Find Similar Products

THROUGH-HOLE RESISTORS




CBT 1/2 5% 10K  
CBT50J10K

Save to List

Find Similar Products

SURFACE MOUNT RESISTORS




3521 150K 1% 2W  
3521150KFT

Save to List

Find Similar Products

WIRE-TO-BOARD CONNECTOR HOUSINGS



10X2 MTE RCPT SR LATCH  
.100CL  
5-103957-1

Save to List

Find Similar Products

