



# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

## TE CONNECTIVITY (TE) 30 50/50 HDR DRST SFMNT TIN

AMPMODU | AMPMODU 50/50 Grid

5-104655-4

TE Internal Number: 5-104655-4

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **1.27 mm [ .05 in ]**

Number of Positions **30**

Header Type **Shrouded**

### Product Drawings

[HEADER ASSEMBLY, SURFACE MOUNT, AMPMODU 50/50 GRID \(6.35\[.250\] MATED HEIGHT\)](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[3D PDF](#)

PDF  
English

### Catalog Pages/Data Sheets

[Ribbon Cable Interconnect Solutions](#)

PDF  
English

[AMPMODU\\_INTERCONNECTION\\_SYSTEM\\_SECTION1AND2](#)

PDF  
English

[Fine Pitch Stacking Connectors - 1.27mm AMPMODU 50/50 Grid Connectors](#)

PDF  
English

[5-1773700-6\\_AMPMODU\\_50\\_50\\_QRG](#)

PDF  
English

### Product Specifications

Application Specification

[AMPMODU 50/50 Grid Connectors For SMT PC Board And IDC Ribbon Cable Applications](#)

PDF  
English

---

## Product Environmental Compliance

TE Material Declaration

[MD\\_5-104655-4\\_102920122334](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Applies To	<b>Printed Circuit Board</b>
	Connector Style	<b>Plug</b>
	PCB Mounting Orientation	<b>Vertical</b>
	Connector Type	<b>Header</b>
	Row-to-Row Spacing	<b>1.27 mm [ .05 in ]</b>
	Stabilizers	<b>Without</b>
	Strain Relief	<b>Without</b>
	Board Standoff	<b>Without</b>
	Profile	<b>Standard</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>

---

Configuration Features	Number of Positions	<b>30</b>
	Number of Rows	<b>2</b>
	Keyed	<b>Yes</b>
	Selectively Loaded	<b>No</b>

---

Electrical Characteristics	Voltage (VAC)	<b>30</b>
	Dielectric Withstanding Voltage	<b>300 VAC</b>

---





Body Features	Header Type	<b>Shrouded</b>
	Hold-Down Post Plating Material	<b>Tin-Lead over Nickel</b>
	Hold-Down Post Plating Thickness	<b>Tin-Lead: 150- Nickel: 50</b>
	Post Size (mm)	<b>.46</b>
	Hold-Down Post Material	<b>Copper Alloy</b>

---

Contact Features	Contact Protection	<b>With</b>
	Contact Shape	<b>Round</b>
	Underplate Material	<b>Nickel</b>

	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µin)	<b>30</b>
	Solder Tail Contact Plating Thickness (µin)	<b>150</b>
	Solder Tail Contact Plating Material	<b>Tin</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Protection Type	<b>Shrouded</b>
	Contact Current Rating (A)	<b>4</b>
<hr/>		
Termination Features	Termination End Plating Thickness (µin)	<b>150</b>
	Termination End Plating Material	<b>Tin</b>
	Termination Method to PC Board	<b>Surface Mount</b>
<hr/>		
Mechanical Attachment	PCB Mounting Style	<b>Surface Mount</b>
	PCB Mount Retention Type	<b>Hold-Down Post(s)</b>
	PCB Mount Retention	<b>With</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment	<b>With</b>
	Mating Connector Lock	<b>Without</b>
	Mating Alignment Type	<b>Keyed</b>
<hr/>		
Housing Features	Centerline	<b>1.27 mm [ .05 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Thermoplastic</b>
	Housing Style	<b>2-Sided</b>
<hr/>		
Dimensions	Shrouded End Dimension (in)	<b>.036</b>
	Stack Height	<b>6.35 mm [ .25 in ]</b>
	Mating Post Length	<b>3.048 mm [ .12 in ]</b>
<hr/>		
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
<hr/>		
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
<hr/>		
Packaging Features	Packaging Quantity	<b>24</b>
	Packaging Method	<b>Tube, Tube/Box</b>

## CUSTOMERS ALSO BOUGHT

<p><b>SURFACE MOUNT RESISTORS</b></p>  <p>CRGH0805 5% 18R 0.33W CRGH0805J18R</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>BOARD-TO-BOARD HEADERS &amp; RECEPTACLES</b></p>  <p>30 50/50 GRID DRST SFMNT RCPT 5-104652-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>MULTIPLE CONFIGURATION PCB HEADERS &amp; RECEPTACLES</b></p>  <p>RP 2A 0.25W 402R 0.1% 25PPM 1K RL 8-2176091-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>MULTIPLE CONFIGURATION PCB HEADERS &amp; RECEPTACLES</b></p>  <p>30 50/50 HDR DRST SFMNT.320 SN 5-104656-3</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
---	--	---	---

Products - 7 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

### RELATIONSHIP

## Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

#### PRODUCT - MATING PRODUCTS



Connectors - W-T-B Headers & Receptacles  
AMPMODU | AMPMODU 50/50 Grid

### 30 50/50 GRID CABLE RECPT - 104893-3

TE INTERNAL NUMBER: 104893-3

✓ Active

Not EU RoHS or ELV Compliant

Centerline **1.27 mm**

Number of Positions **30**

Number of Rows **2**

Contact Mating Area Plating

Material **Gold**

Contact Mating Area Plating

Thickness **.762 µm**

#### PRODUCT - MATING PRODUCTS



Connectors - PCB Connector Covers  
AMPMODU | AMPMODU 50/50 Grid

### 30 50/50 GRID CABLE RCPT COVER - 104891-3

TE INTERNAL NUMBER: 104891-3

✓ Active

Always EU RoHS/ELV Compliant

Centerline **1.27 mm**

Number of Positions **30**

Number of Rows **2**

Body Material **Polyester**

Row-to-Row Spacing **1.27 mm**

RELATIONSHIP

## Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - Board-to-Board Headers & Receptacles

AMPMODU I AMPMODU 50/50 Grid

**30 50/50 GRID SMT RCPT  
VC LF - 5-147384-3**

TE INTERNAL NUMBER: 5-147384-3

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline **1.27 mm**

Number of Positions **30**

Packaging Method **Tape & Reel**

Contact Mating Area Plating

Material **Gold**



RELATIONSHIP

## Mating Products

Used to identify Mating Parts

[See All Mating Products](#)



PRODUCT - MATING PRODUCTS

Connectors - Board-to-Board Headers & Receptacles

AMPMODU I AMPMODU 50/50 Grid

**30 50/50 GRID RCPT VC  
W/O HD - 147413-4**

TE INTERNAL NUMBER: 147413-4

✓ Active

Not EU RoHS or ELV Compliant

Connector Style **Receptacle**

Centerline **1.27 mm**

Number of Positions **30**

Packaging Method **Tape & Reel**

Contact Mating Area Plating

Material **Gold**

