



HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

08 MTE HDR SRRA SMT.100CL

AMP | AMPMODU MTE

5-147324-7

TE Internal Number: 5-147324-7

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **8**

PCB Mounting Orientation **Right Angle**

PCB Mounting Style **Surface Mount**

Number of Rows **1**

Product Drawings

[HEADER ASSEMBLY, LATCHING, RIGHT ANGLE SURFACE MOUNT, MTE, AMPMODU](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[AMPMODU_INTERCONNECTION_SYSTEM_SECTION5_CONT](#)

PDF
English

[AMPMODU MTE INTERCONNECT SYSTEM](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5-147324-7_04112011036](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Right Angle
	Product Type	Connector
	Row-to-Row Spacing	2.54 mm [.1 in]
	Connector Type	Header
	Strain Relief	Without
	Connector Style	Plug
	PCB Orientation Feature	No
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	8
	Number of Rows	1
	Backwall/Post Interruptions	Without
Electrical Characteristics	Dielectric Withstanding Voltage	600 V
	Termination Resistance	15 MΩ
	Insulation Resistance	5000 MΩ
Body Features	Header Type	Shrouded
Contact Features	Contact Mating Area Plating Material	Tin
	Contact Mating Area Plating Thickness	2.54 – 5.08 μm [100 – 200 μin]
	Contact Type	Pin
	Solder Tail Contact Plating Material	Tin
	Contact Termination Area Plating Thickness	2.54 – 5.08 μm [100 – 200 μin]
	Tail Plating Thickness	2.54 – 5.08 μm [100 – 200 μin]
	Contact Current Rating (A)	3
	Contact Shape	Square
	Tail Plating Material	Tin
	Contact Termination Area Plating Material	Tin
	Contact Termination Area Plating Material Finish	Matte
	Contact Base Material	Brass
Termination Features	Termination Method to Wire/Cable	Crimp, Insulation Displacement Crimp (IDC)
Mechanical Attachment	PCB Mounting Style	Surface Mount
	PCB Mount Alignment	Without
	Mating Retention	With

	Mating Retention
	PCB Mount Retention	With
	Panel Mount Retention	Without
	Mating Alignment Type	Latched
	Mating Alignment	With
	Mating Retention Type	Polarized Lock
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
<hr/>		
Dimensions	Tail Length	3.05 mm [.12 in]
	Mating Post Length	5.84 mm [.23 in]
	Length	25.4 mm [1 in]
	Height	13.59 mm [.535 in]
<hr/>		
Usage Conditions	Temperature Rating	High
	Operating Temperature Range (°C)	-65 – 105
<hr/>		
Operation/Application	For Use With	Receptacle Housing Assembly
	Pick and Place Cover	Without
<hr/>		
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, UL E28476
<hr/>		
Packaging Features	Packaging Method	Tape & Reel
	Packaging Quantity	300
<hr/>		
Other	Comment	Use Keying Tool No. 91417-1 to remove post for keying.
<hr/>		
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

[SURFACE MOUNT DEVICES](#)

[THROUGH-HOLE RESISTORS](#)

[SURFACE MOUNT RESISTORS](#)

[SURFACE MOUNT RESISTORS](#)



MPR20 2R2 5% 100PPM
MPR20A2R2J







RN 0603 12K4 0.1% 10PPM
CUT LENGTH
RN73C1J12K4BTG







RN 0603 30K1 0.1% 10PPM
CUT LENGTH
RN73C1J30K1BTG

PICOSMDC050S-2
PICOSMDC050S-2

 Save to List
 Find Similar Products

 Save to List
 Find Similar Products

 Save to List
 Find Similar Products

 Save to List
 Find Similar Products

