




MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

AMPMODU II PIN HEADER 50P

AMPMODU | AMPMODU Headers

5-826632-0

TE Internal Number: 5-826632-0

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **100**

Header Type **Breakaway**

Product Drawings

AMPMODU II STIFTLISTE ZWEIREIHIG

PDF
English

CAD Files

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

3D PDF

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Vertical

Connector Type

Header

Row-to-Row Spacing

2.54 mm [.1 in]

Stabilizers

Without

Strain Relief

Without

	Board Standoff	Without
	Profile	Standard
	Product Type	Connector
	Gasket	Without
<hr/>		
Configuration Features	Number of Positions	100
	Number of Rows	2
	Keyed	No
	Selectively Loaded	No
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	1000 V
<hr/>		
Body Features	Header Type	Breakaway
	Post Size	.63 mm [.024 in]
<hr/>		
Contact Features	Contact Protection	Without
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin
	Contact Mating Area Plating Thickness (µm)	.8
	Contact Mating Area Plating Material	Gold
	Contact Current Rating (A)	5
<hr/>		
Termination Features	Termination Post Length	3.2 mm [.1259 in]
	Termination End Plating Material	Tin
	Termination End Plating Thickness (µm)	3
	Termination Method to PC Board	Through Hole
<hr/>		
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Connector Lock	Without
<hr/>		
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Green

Housing Color	Green
Housing Material	PBT GV

Dimensions	Mating Post Length	6.7 mm [.264 in]
------------	--------------------	---------------------------

Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Housing	No

Operation/Application	High Speed Serial Data Connector	No
-----------------------	----------------------------------	-----------

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------





Packaging Features	Packaging Quantity	150
	Packaging Method	Box/Carton

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

FFC CONNECTORS	SURFACE MOUNT RESISTORS	RIBBON CABLE CONNECTORS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES
 <p>TRIOMATE ASY H 11P L=2.54 LDFR 6-520314-1</p> <p>Save to List Find Similar Products</p>	 <p>CRGH2512 5% 82R 2W CRGH2512J82R</p> <p>Save to List Find Similar Products</p>	 <p>016 2MM 30DP FT 2-111626-5</p> <p>Save to List Find Similar Products</p>	 <p>50P AMPMODU II PIN HDR. 5-826629-0</p> <p>Save to List Find Similar Products</p>