



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)
MOD.HSG 50 P.
AMPMODU | AMPMODU IV/V

5-925369-0
TE Internal Number: 5-925369-0

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [.1 in]**

Number of Positions **50**

Number of Rows **1**

Row-to-Row Spacing **2.54 mm [.1 in]**

Color **Green**

Product Drawings

[AMPMODU IV GEHAEUSE, EINREIHIG](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

Product Specifications

Product Specification

[AMPMODU Mod 1/2 Wire To Board Standard Pressure Contact Interconnection System](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Row-to-Row Spacing **2.54 mm [.1 in]**













Connector Style **Receptacle**

Glow Wire Rating **Standard Part - Not Glow Wire**

Strain Relief **With**

	Connector Type	Housing
	Product Type	Connector
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	50
	Number of Rows	1
Electrical Characteristics	Operating Voltage	250 VAC
Body Features	Color	Green
Contact Features	Contact Layout	Inline
	Contact Type	Socket
Termination Features	Termination Method to Wire/Cable	Crimp
Mechanical Attachment	Mating Retention	With
	Mating Retention Type	Lock
	Mating Connector Lock	Without
	Mating Alignment	Without
	Mating Alignment Type	Polarization
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	PA 6.6
	Housing Configuration	Both Ends Closed
	Housing Color	Green
Dimensions	Height (in)	.11
	Length (in)	4.99
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
Operation/Application	For Use With	AMPMODU Mod II .025 inch Headers
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	50

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	WIRE-TO-BOARD CONNECTOR CONTACTS	TOGGLE SWITCHES	WIRE-TO-BOARD CONNECTOR HOUSINGS
 <p>ULTRAFAST 187 ASSY REC 16-14 TPBR LP 3-520125-2</p> <hr/> <p> Save to List  Find Similar Products</p>	 <p>MOD-4 REC.CONT.SCP. 1-141708-1</p> <hr/> <p> Save to List  Find Similar Products</p>	 <p>A201SYCQ04 2-1825138-5</p> <hr/> <p> Save to List  Find Similar Products</p>	 <p>MOD 4 REC.HSG 1X06P 925366-6</p> <hr/> <p> Save to List  Find Similar Products</p>