




# RIBBON CABLE CONNECTORS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## A/L LOW PRO HDR 40P VERT BLACK

AMP-LATCH | Low Profile Headers

5103308-8

TE Internal Number: 5103308-8

Always EU RoHS/ELV Compliant

Centerline **2.54 mm [ .1 in ]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Through Hole**

Shrouded **Yes**

### Product Drawings

[HEADER ASSY, VERTICAL, LOW PROFILE, AMP-LATCH](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

[Ribbon Cable Interconnect Solutions](#)

PDF  
English

[AMPMODU\\_INTERCONNECTION\\_SYSTEM\\_SECTIONS](#)

PDF  
English

[7-1773458-6\\_AMPLATCH\\_QRG](#)

PDF  
English

### Product Specifications

Product Specification

[AMP-LATCH And IDC Header Connectors, .100 X .100 Inch Grid](#)

PDF  
English

Qualification Test Report

[Connector, AMP-LATCH Header, .100 X .100 Inch Grid](#)

PDF  
English

### Product Environmental Compliance

TE Material Declaration

[MD\\_5103308\\_8\\_08202014228\\_data](#)

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	<b>Vertical</b>
	Shrouded	<b>Yes</b>
	Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
	Connector Style	<b>Plug</b>
	Profile	<b>Low</b>
	Applies To	<b>Printed Circuit Board</b>
	Product Type	<b>Connector</b>
	Board Standoff	<b>Without</b>
	Connector Type	<b>Header</b>
	Connector System	<b>Wire-to-Board</b>
	Ejection Latches	<b>Without</b>
Configuration Features	Number of Positions	<b>40</b>
	Number of Rows	<b>2</b>
Electrical Characteristics	Operating Voltage (VAC)	<b>250</b>
	Insulation Resistance (MΩ)	<b>5000</b>
Body Features	Post Size	<b>.64 mm [ .025 in ]</b>
	Header Type	<b>Pin Header</b>
	Daisy Chain	<b>With</b>
Contact Features	Contact Mating Area Plating Material	<b>Gold Flash over Palladium Nickel, Gold</b>
	Contact Design	<b>Square Post</b>
	Contact Shape	<b>Square</b>
	Contact Transmits (Typical)	<b>Signal (Data)</b>
	Solder Tail Contact Plating Material	<b>Tin over Nickel</b>
	Contact Current Rating (A)	<b>1</b>
	Contact Base Material	<b>Copper Alloy</b>
	Contact Mating Area Plating Thickness (µin)	<b>15</b>
	Contact Type	<b>Pin</b>

Contact Termination Area Plating Material	<b>Tin</b>
Contact Termination Area Plating Thickness	<b>2.54 µm [ .100 in ]</b>

---

Termination Features	Termination Method to PC Board	<b>Through Hole</b>
	Termination Post Length	<b>3.05 mm [ .12 in ]</b>

---

Mechanical Attachment	PCB Mount Retention	<b>Without</b>
	Mating Alignment Type	<b>Center, Dual Polarizing Bar</b>
	Mating Connector Lock	<b>Without</b>
	Mating Alignment	<b>With</b>
	Polarization	<b>With</b>
	Panel Mount Retention	<b>Without</b>
	Mating Retention	<b>Without</b>
	PCB Mount Alignment	<b>Without</b>

---

Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>
	Housing Style	<b>4-Sided</b>
	Housing Material	<b>Glass Filled Nylon/PBT</b>

---

Dimensions	Height	<b>8.813 mm [ .347 in ]</b>
	Length	<b>58.42 mm [ 2.3 in ]</b>
	Shrouded End Dimension	<b>3.81 mm [ .15 in ]</b>

---

Usage Conditions	Temperature Rating	<b>Standard</b>
	Operating Temperature Range (°C)	<b>-65 – 105</b>

---

Operation/Application	For Use With	<b>Mates with Receptacles</b>
-----------------------	--------------	-------------------------------

---

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
--------------------	------------------------	-----------------

---





Packaging Features	Packaging Method	<b>Tube</b>
	Packaging Quantity	<b>35</b>

---

Product Compliance [Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

RIBBON CABLE CONNECTORS	PCB CONNECTOR COVERS	WIRE-TO-BOARD HEADERS & RECEPTACLES	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES
 <p><b>A/L LOW PRO HDR 50P VERT BLACK</b> 1-5103308-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>20 AMPMODU MT COVER DR .100CL</b> 102537-8</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>10 MTE HDR SRST LATCH W/HLDWN</b> 103670-9</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	 <p><b>40 MODII HDR SRST B/A .100CL</b> 4-103747-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>

Products - 13 Results

[View All](#)

[Compare 0/10](#)



Relation Type ▼

RELATIONSHIP

### Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS		
	<p>Connectors - Ribbon Connector Accessories AMP-LATCH   AMP-LATCH - NOVO</p> <p><b>040 STRAIN RELIEF A-L RCPT - 499252-1</b> TE INTERNAL NUMBER: 499252-1 ALIAS ID: 1100632, 406420158</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Accessory Type <b>Strain Relief</b></p>
	<p>Connectors - Ribbon Cable Connectors AMP-LATCH   AMP-LATCH - NOVO</p> <p><b>40 NOVO MIL/CTR 30DP, LEAD FREE - 1658622-9</b> TE INTERNAL NUMBER: 1658622-9</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Centerline <b>2.54 mm</b></p> <p>PCB Mount Retention <b>Without</b></p> <p>PCB Mounting Orientation <b>Vertical</b></p> <p>Termination Method to PC Board <b>Through Hole - Solder</b></p> <p>Termination Method to Wire/Cable <b>Insulation Displacement Crimp (IDC)</b></p>

RELATIONSHIP

### Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors  
AMP-LATCH | AMP-LATCH - NOVO

**622-4041LF FEM SOCKET,  
LEAD FREE - 1-1658527-3**  
TE INTERNAL NUMBER: 1-1658527-3

✓ Active

Always EU RoHS/ELV Compliant

Number of Positions **40**

Connector Style **Receptacle**



RELATIONSHIP

**Mating Products**

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors  
AMP-LATCH | AMP-LATCH - NOVO

**40 NOVO DUAL 30DP,  
LEAD FREE - 1658624-9**  
TE INTERNAL NUMBER: 1658624-9

✓ Active

Always EU RoHS/ELV Compliant

Centerline **2.54 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

**Vertical**

Termination Method to PC Board

**Through Hole - Solder**

Termination Method to

Wire/Cable **Insulation**

**Displacement Crimp (IDC)**



PRODUCT - MATING PRODUCTS



Connectors - Ribbon Connector Accessories  
AMP-LATCH | AMP-LATCH - NOVO

**040 STRAIN RELIEF A-L  
RCPT - 499252-1**  
TE INTERNAL NUMBER: 499252-1  
ALIAS ID: 1100632, 406420158

✓ Active

Always EU RoHS/ELV Compliant

Accessory Type **Strain Relief**

