




BOARD-TO-BOARD HEADERS & RECEPTACLES



TE CONNECTIVITY (TE)
1FHP,64,30A/S,N,C,S10,12,13,15
1.0mm FH | 1mm FH

5120534-1
TE Internal Number: 5120534-1

Always EU RoHS/ELV Compliant

Connector Style **Plug**

Centerline **.63 mm [1 in]**

Stack Height (mm) **10, 12, 13, 15**

Stack Height (in) **.591**

Number of Positions **64**

Packaging Method **Tape & Reel**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[PLUG ASSY, W/COVER 1.0mm FH\(IEEE1386\) CONNECTOR](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[Fine Pitch Stacking Connectors - 1.0mm Free Height \(FH\) \(IEEE 1386\) Connectors](#)

PDF
English

[Solutions For AdvancedTCA, AdvancedTCA 300, MicroTCA, And AdvancedMC Standards Datasheet 3-1773445-8](#)

PDF
English

[2-1773454-6_Stacking_Connectors](#)

PDF
English

Product Specifications

Product Specification

[1.0 Mm Mezzanine Connectors](#)

PDF
English

Application Specification

[1.0 Mm Free Height \(FH\) Plug And Receptacle Connectors Using Surface Mount Technology \(SMT\)](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5120534-1_021420142354_dmtec](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Plug
	Board-to-Board Configuration	Mezzanine
	PCB Mounting Orientation	Vertical
	Boss	Without
	Connector System	Board-to-Board
	Connector Type	Connector Assembly
	Row-to-Row Spacing (mm)	1
	Applies To	Printed Circuit Board
	Product Type	Connector
	Series	1mm FH

Configuration Features	Number of Positions	64
	Number of Columns	32
	Stackable	Yes
	Number of Rows	2
	Solder Tail Orientation	Inline

Electrical Characteristics	Voltage (VAC)	250
----------------------------	---------------	------------

Signal Characteristics	Differential Signaling	Yes
------------------------	------------------------	------------

Contact Features	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness	.76 µm [29.92 µin]
	Contact Termination Area Plating Thickness	3.81 µm [150 µin]
	Contact Current Rating (A)	1
	Contact Configuration	Single Beam
	Solder Tail Contact Plating Material	Tin over Nickel
	Underplate Material Thickness	1.27 µm [50 µin]
	Solder Tail Contact Plating Thickness	3.81 µm [150 µin]
	Underplate Material	Nickel

Contact Transmits (Typical)	Signal (Data)
Contact Type	Pin
Contact Termination Area Plating Material	Tin
Contact Layout	Inline
Contact Base Material	Phosphor Bronze
Contact Termination Area Plating Material Finish	Matte

Termination Features	Termination Method to PC Board	Surface Mount
----------------------	--------------------------------	----------------------

Mechanical Attachment	Mating Alignment	Without
	Mating Alignment Type	Polarizing Tab
	PCB Mount Retention	Without
	PCB Mount Retention Type	None
	PCB Mount Alignment	Without
	PCB Mount Alignment Type	Locating Posts
	Mating Retention	Without

Housing Features	Centerline	.63 mm [1 in]
	Housing Color	Black
	Housing Material	Thermoplastic
	Housing Entry Style	Top

Dimensions	Stack Height (mm)	10, 12, 13, 15
	Stack Height (in)	.591
	Width	6.04 mm [.238 in]
	Length	34.22 mm [1.347 in]
	Mating Post Length	4.27 mm [.168 in]
	Tail Length	2.05 mm [.081 in]
	Height	8.38 mm [.329 in]

Usage Conditions	Operating Temperature Range	-55 – 110 °C [-67 – 230 °F]
	Housing Material Temperature	High

Operation/Application	Pick and Place Cover	With
	For Use With	Receptacle Assembly

Industry Standards	Agency/Standard	CSA, UL
--------------------	-----------------	----------------

UL File Number	E28476
Industry Standard	IEEE 1386 Mezzanine Connector
CSA Certified	Yes
UL Rating	Listed
UL Flammability Rating	UL 94V-0
CSA File Number	LR7189





Packaging Features	Packaging Method	Tape & Reel
	Packaging Quantity	400

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p>  <p>1FHR, 64, 30A/S, N, C, S14, 15 5120531-1</p> <p>Save to List Find Similar Products</p>	<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p>  <p>Mezalok, Socket, 114 p, 12 mm, 50 Au, LF 2102061-4</p> <p>Save to List Find Similar Products</p>	<p>BOARD-TO-BOARD HEADERS & RECEPTACLES</p>  <p>1FHR, 64, 30A/S, N, C, S08, 09, 10 5120528-1</p> <p>Save to List Find Similar Products</p>	<p>RJ45 CONNECTORS</p>  <p>IMJ, 1X1, P GRD, INSLT, LED(G/Y)SN 1-406507-1</p> <p>Save to List Find Similar Products</p>
--	--	--	--

Products - 12 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Board-to-Board Headers & Receptacles 1.0mm FH 1mm FH</p> <p>1FHR, 64, 30A/S, N, C, S13 - 5120530-1</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Connector Style Receptacle</p> <p>Centerline .63 mm</p> <p>Stack Height 13 mm</p>	<input checked="" type="checkbox"/>
---	--	---	-------------------------------------

TE INTERNAL NUMBER: 5120530-1

✓ Active

Stack Height **10 mm**

Number of Positions **64**

Packaging Method **Tape & Reel**


RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Board-to-Board Headers & Receptacles

1.0mm FH | 1mm FH

**1FHR, 64, 30A/S, S, N,
S08, 09, 10 - 5120521-1**

TE INTERNAL NUMBER: 5120521-1

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline **.63 mm**

Stack Height **8 mm, 9 mm, 10 mm**

Number of Positions **64**

Packaging Method **Tape & Reel**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Board-to-Board Headers & Receptacles

1.0mm FH | 1mm FH

**1FHR, 64, 30A/S, N, C,
S14, 15 - 5120531-1**

TE INTERNAL NUMBER: 5120531-1

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline **.63 mm**

Stack Height **14 mm, 15 mm**

Number of Positions **64**

Packaging Method **Tape & Reel**

