




CRIMP RINGS & SPADES



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

TERMINAL R PG 4 10

PLASTI-GRIP

52043-2

TE Internal Number: 52043-2

Alias ID: A27058-000, AMPS-0-0052043-2

Always EU RoHS/ELV Compliant

Terminal Shape **Ring Tongue**

Stud Diameter **5 mm [.197 in]**

Tongue Thickness **1.22 mm [.048 in]**

Sealed **No**

Heavy Duty **No**

Product Drawings

[TERMINAL, RING TONGUE, PLASTI-GRIP, WIRE SIZE: 4 AWG](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[PLASTI GRIP_QRG](#)

PDF
English

Product Specifications

Application Specification

[PLASTI-GRIP Terminals And Splices](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_52043-2_01142014849_dmtec](#)

PDF
English

Instruction Sheets

Instruction Sheet (U.S.)

[PLASTI-GRIP Pressure Type Straight And 90-Degree Bent Terminals \(Use Tooling For AMPLI-BOND Connectors\)](#)





PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	No
	Barrel Type	Closed Barrel
	Wire/Cable Type	Regular Wire
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
	Stud Size	10
	Shape Code	RING-044
	Barrel Style	Standard
	Wire/Cable Composition	Stranded
Configuration Features	Terminal Angle	Straight
	Number of Holes	1
Electrical Characteristics	Voltage (Max) (V)	600
Body Features	Plating Material	Copper, Tin
	Insulation Material	PVC
	Inspection Slot	No
Contact Features	Terminal Shape	Ring Tongue
	Terminal Orientation	Straight
Dimensions	Stud Diameter	5 mm [.197 in]
	Tongue Thickness	1.22 mm [.048 in]
	Wire Insulation Diameter (Max)	11.43 mm [.45 in]
	Wire Size (AWG)	4
	Wire Size (mm ²)	21.2
	Wire Size (CMA)	33100 – 52600
	Barrel Inside Diameter (in)	.45
	Overall Length (in)	1.948
Usage Conditions	Operating Temperature Range (°C)	105

Usage Conditions	Operating Temperature Range (°C)	100
Operation/Application	Heavy Duty	No
Industry Standards	Government Qualified	No
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	100
Other	Barrel Color	Yellow
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

SPLICES	CRIMP RINGS & SPADES	PRE-PRINTED CABLE MARKERS	PRE-PRINTED CABLE MARKERS
 <p>D-150-0180 594677-000</p> <p>Save to List Find Similar Products</p>	 <p>TERMINAL R PG 2 1/4 52267-1</p> <p>Save to List Find Similar Products</p>	 <p>06173928 EC0949-000</p> <p>Save to List Find Similar Products</p>	 <p>06173915 EC0936-000</p> <p>Save to List Find Similar Products</p>