



## BNC CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### PCB-BNC RT ANGLE JACK W/O POST

PCF , PCH

5226990-6

TE Internal Number: 5226990-6

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Panel Mount Retention **With**

PCB Mount Retention **Without**

PCB Termination Method **Through Hole**

Body Material **Polyester, PBT**

#### Product Drawings

[JACK, PANEL, RIGHT ANGLE, 50 OHM, PCB, SERIES BNC](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[BNC Connectors](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

Applies To

**Printed Circuit Board**

Sealed

**No**

RF Connector Type

**BNC**

Connector Style

**Jack**

PCB Mounting Orientation

**Right Angle**

Dielectric Material

**Polymethylpentene**

|                     |                       |
|---------------------|-----------------------|
| Dielectric Material | <b>Polyethylene</b>   |
| ESD Protection      | <b>Without</b>        |
| Isolated Ground     | <b>No</b>             |
| Grade               | <b>Commercial</b>     |
| Product Type        | <b>Connector - RF</b> |

---

|                        |                 |                |
|------------------------|-----------------|----------------|
| Configuration Features | Solder Terminal | <b>Without</b> |
|                        | Number of Ports | <b>1</b>       |

---

|                            |                        |            |
|----------------------------|------------------------|------------|
| Electrical Characteristics | 50 Ohm                 | <b>Yes</b> |
|                            | 75 Ohm                 | <b>No</b>  |
|                            | Impedance ( $\Omega$ ) | <b>50</b>  |

---

|               |                 |                       |
|---------------|-----------------|-----------------------|
| Body Features | Body Material   | <b>Polyester, PBT</b> |
|               | Body Style      | <b>Right Angle</b>    |
|               | Body Insulation | <b>Without</b>        |
|               | Color           | <b>Black</b>          |

---

|                  |   |                        |
|------------------|---|------------------------|
| Contact Features | Center Contact Material                             | <b>Phosphor Bronze</b> |
|                  | Center Contact Plating Material                     | <b>Gold</b>            |
|                  | Center Contact Plating Thickness ( $\mu\text{in}$ ) | <b>30</b>              |

---

|                      |                        |                     |
|----------------------|------------------------|---------------------|
| Termination Features | PCB Termination Method | <b>Through Hole</b> |
|----------------------|------------------------|---------------------|

---

|                       |                        |                   |
|-----------------------|------------------------|-------------------|
| Mechanical Attachment | Panel Mount Retention  | <b>With</b>       |
|                       | PCB Mount Retention    | <b>Without</b>    |
|                       | Panel Mount            | <b>With</b>       |
|                       | Polarized              | <b>No</b>         |
|                       | Panel Attachment Style | <b>Rear Mount</b> |
|                       | Hardware Included      | <b>No</b>         |

---

|            |                  |                             |
|------------|------------------|-----------------------------|
| Dimensions | Height above PCB | <b>15.88 mm [ .625 in ]</b> |
|------------|------------------|-----------------------------|

---









|                    |                  |             |
|--------------------|------------------|-------------|
| Packaging Features | Packaging Method | <b>Tube</b> |
|--------------------|------------------|-------------|

---

|       |         |  |
|-------|---------|--|
| Other | Comment | <b>If an Insulating Bushing is required, see Part Number 330620.</b> |
|-------|---------|--|

---

## CUSTOMERS ALSO BOUGHT

| DIP & SIP SWITCHES  | WIRE-TO-BOARD HEADERS & RECEPTACLES   | DIP & SIP SWITCHES  | RIBBON CABLE CONNECTORS   |
|---|---|---|---|
| DIP SW 10POSN AU<br>5435640-7   | 11 MTE HDR SRST LATCH<br>W/HLDWN<br>6-103669-0  | DIP SW 12 POSN AU<br>3-435640-2   | 050 UNIV HDR SP 4S 15DP<br>STD<br>1-102153-0  |
|  Save to List<br> Find Similar Products |  Save to List<br> Find Similar Products |  Save to List<br> Find Similar Products |  Save to List<br> Find Similar Products |