



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## BNC PCB VERTICAL JACK W/POST

PCF , PCH

5227673-1

TE Internal Number: 5227673-1

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Panel Mount Retention **With**

Panel Mount Retention Type **Lockwasher and Nut**

PCB Mount Retention **With**

PCB Termination Method **Through Hole**

### Product Drawings

[JACK, VERTICAL, PCB, 50 OHM, SERIES BNC](#)

PDF (TIFF AVAILABLE)  
English

[JACK, VERTICAL, PCB, 50 OHM, SERIES BNC](#)

PDF (TIFF AVAILABLE)  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[3D PDF](#)

PDF  
English

### Catalog Pages/Data Sheets

[BNC Connectors](#)

PDF  
English

### Product Environmental Compliance

TE Material Declaration

[MD\\_5227673-1\\_12122015015\\_dmtec](#)


PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Sealed	<b>No</b>
	RF Connector Type	<b>BNC</b>
	Connector Style	<b>Jack</b>
	PCB Mounting Orientation	<b>Vertical</b>
	Dielectric Material	<b>Polymethylpentene</b>
	ESD Protection	<b>Without</b>
	Isolated Ground	<b>No</b>
	Grade	<b>Commercial</b>
	Product Type	<b>Connector - RF</b>
<hr/>		
Configuration Features	Solder Terminal	<b>Without</b>
	Number of Ports	<b>1</b>
<hr/>		
Electrical Characteristics	50 Ohm	<b>Yes</b>
	75 Ohm	<b>No</b>
	Impedance ( $\Omega$ )	<b>50</b>
<hr/>		
Body Features	Body Material	<b>Zinc</b>
	Body Plating Material	<b>Nickel</b>
	Body Insulation	<b>Without</b>
<hr/>		
Contact Features	Center Contact Material	<b>Phosphor Bronze</b>
	Center Contact Plating Material	<b>Gold</b>
	Center Contact Plating Thickness ( $\mu\text{in}$ )	<b>889</b>
<hr/>		
Termination Features	PCB Termination Method	<b>Through Hole</b>
<hr/>		
Mechanical Attachment	Panel Mount Retention	<b>With</b>
	Panel Mount Retention Type	<b>Lockwasher and Nut</b>
	PCB Mount Retention	<b>With</b>
	Panel Mount	<b>With</b>
	Polarized	<b>No</b>
	Mounting Post Length	<b>3.48 mm [ .137 in ]</b>
	Mounting Post Style	<b>Standard</b>
	Panel Attachment Style	<b>Rear Mount</b>
	Hardware Included	<b>No</b>

Dimensions	Height above PCB	<b>34.93 mm [ 1.375 in ]</b>
Packaging Features	Packaging Method	<b>Tray</b>
Other	Comment	<b>If an Insulating Bushing is required, see Part Number 330620.</b>
Product Compliance	<a href="#">Statement of Compliance PDF</a> <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## CUSTOMERS ALSO BOUGHT

SURFACE MOUNT RESISTORS	FPC CONNECTORS	POWER CONTACTS	SURFACE MOUNT RESISTORS
 <p><b>RLP73K 3A R24 1% 1K RL</b> RLP73K3AR24FTDF</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>1MM FPC HORZ.TOP</b> <b>CONT.ASSY 17P</b> 1-84953-7</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>MINI UMN2 SOK 22-</b> <b>18AWG LP LF</b> 1-794229-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>3520 470R 5%</b> 3520470RJT</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>