



## CRIMP RINGS & SPADES



Active

PRODUCT DRAWING  
English

TE CONNECTIVITY (TE)

### TERMINAL,PG SPR SPD 16-14 10

PLASTI-GRIP | PLASTI-GRIP

52465

TE Internal Number: 52465

Always EU RoHS/ELV Compliant

Terminal Shape **Spring Spade**

Stud Diameter **4.82 mm [ .19 in ]**

Tongue Thickness **.84 mm [ .033 in ]**

Sealed **No**

Heavy Duty **No**

#### Product Drawings

[TERMINAL, SPRING SPADE, LONG, PLASTI-GRIP, WIRE SIZE: 16-14](#)

PDF (TIFF AVAILABLE)  
English

[TERMINAL, SPRING SPADE, LONG, PLASTI-GRIP, WIRE SIZE: 16-14](#)

PDF (TIFF AVAILABLE)  
English

#### Catalog Pages/Data Sheets

[PLASTI GRIP\\_QRG](#)

PDF  
English

#### Product Specifications

##### Application Specification

[PLASTI-GRIP Terminals And Splices](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

#### Product Type Features

Sealed	<b>No</b>
Barrel Type	<b>Closed Barrel</b>
Wire/Cable Type	<b>Regular Wire</b>
Insulated	<b>Yes</b>
Insulated Wire Support	<b>Yes</b>
Support Style	<b>Insulation Support</b>
Stud Size	<b>10</b>
Shape Code	<b>SPADE-032</b>
Barrel Style	<b>Standard</b>

Wire/Cable Composition

**Solid or Stranded**

Configuration Features

Terminal Angle

**Straight**

Electrical Characteristics

Voltage (Max) (V)

**600**

Body Features

Plating Material

**Phosphor Bronze, Tin**

Insulation Sleeve Color

**Blue**

Insulation Material

**Vinyl**

Body Style

**Long**

Inspection Slot

**No**

Insulation Support Sleeve Material

**PVC**

Contact Features

Terminal Shape

**Spring Spade**

Terminal Orientation

**Straight**

Dimensions

Stud Diameter

**4.82 mm [ .19 in ]**

Tongue Thickness

**.84 mm [ .033 in ]**

Wire Insulation Diameter (Max) (in)

**.193**

Wire Insulation Diameter

**3 – 4.9 mm [ .118 – .193 in ]**

Wire Size (AWG)

**16 – 14**

Wire Size (mm<sup>2</sup>)

**1.25 – 2**

Wire Size (CMA)

**2050 – 5180**

Barrel Inside Diameter (in)

**.195**

Overall Length (in)

**1.017**

Operation/Application

Heavy Duty

**No**

Industry Standards

Government Qualified

**No**

Packaging Features

Packaging Method

**Loose Piece**

Packaging Quantity

**1000**

Other

Barrel Color













**Blue**

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW FULL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

CRIMP RINGS & SPADES	ROTARY SWITCHES	CRIMP QUICK DISCONNECTS	RECTANGULAR POWER CONNECTORS
 <p>TERMINAL, PG SPR SPD 16-14 6 52463</p>	 <p>DRW1604=Rot Dip, w/Wheel 3-1825033-1</p>	 <p>.205 FAST REC IS 22-18 TPBR 42299-2</p>	 <p>18P MINI UMNL2 PLUG HSG UL94V0 794208-1</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>