

## BOARD-TO-BOARD JUMPERS & SHUNTS



✓ Active

PRODUCT DRAWING
English
3D PDF

TE CONNECTIVITY (TE) SHUNT,.200 C/L, 2 POS, SN AMP | L У 🖬 f v

531230-4 TE Internal Number: 531230-4

## Always EU RoHS/ELV Compliant

Shunt Type **Standard Housing** Shunt Style **Open Top** 

Centerline 5.08 mm [.2 in ]

Number of Positions 2

Product Drawings	LOW PROFILE SHUNT CONNECTOR 5.08 [.200] CL PDF English	
CAD Files	3D PDF PDF English	
	Customer View Model 3D_IGS.ZIP English	
	Customer View Model 3D_STP.ZIP English	
	Customer View Model 2D_DXF.ZIP English	
Product Specifications		
Product Specification	Low Profile Shunt Connector	
Application Specification	English Low Profile, Economy, Dual Beam,And Multiposition Shunt Connectors PDF English	
	Low Profile, Economy, Dual Beam,And Multiposition Shunt Connectors TIF English	

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Low

Product Type

Shunt

Configuration Features	Number of Positions	2
Electrical Characteristics	Insulation Resistance (M $\Omega$ )	1000
Body Features	Handle	Without
Contact Features	Shunt Type	Standard Housing
	Shunt Style	Open Top
	Contact Current Rating (A)	3
	Contact Base Material	Beryllium Copper
	Contact Mating Area Plating Thickness	2.54 µm [ 100 µin ]
	Contact Mating Area Plating Material	Tin
Housing Features	Centerline	5.08 mm [ .2 in ]
	Housing Material	Polyester - GF
	Housing Color	Black
Dimensions	Height	6.35 mm [ .25 in ]
Usage Conditions	Operating Temperature Range (°C)	-40 – 85
Industry Standards	UL Rating	Recognized
	CSA Certified	Yes
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Вох
	Packaging Quantity	2000
Product Compliance		

Product Compliance

Statement of Compliance PDF

VIEW ALL PRODUCT COMPLIANCE

## CUSTOMERS ALSO BOUGHT

BOARD-TO-BOARD JUMPERS & TERMINATORS RADIAL-LEADED DEVICES HDMI CONNECTORS

